

## General informations

Battery name	IT4 AGM
Product Range	ITINERIS AGM - Stop & Start: Absorptive glass mat
European Type No. (ETN)	580.901.080
Polarity	DX
Technology	AGM
Application	Stop & Start
Standard ref.	EN 50342-1; EN 50342-2



The new Midac battery that completes our line of products for Stop&Start motors with braking energy recovery. The AGM (Absorptive Glass Mat) battery's electrolyte is completely absorbed by the separator, so that the acid is retained even if the unit is overturned for a long period of time. Gas recombination technology and the use of caps with valves on each cell enable the battery to be installed in the passenger and luggage compartments. The design of the grilles and the composition of the active material makes it especially suited to cyclic applications.

## General characteristics

Voltage (V)	12
Capacity 20h (Ah)	80
Cold cranking Amps (CCA), EN (A)	800
Energy at 20hrs rate and 25C (Wh)	956
Cranking Power 10" at -18°C (KW)	6,2

Dimensional group	LN4
Sizes (LxWxH) (mm)	310 x 175 x 190
Base Hold-Down	B3(f)
Lay-out/Terminals	0 / 1
Battery weight $\pm$ 5% (kg)	23,6

## Box

Case	PP/PE
Lid	PP/PE
Plug	PP/PE

Colour	Black
Colour	Black
Colour	Black

## Drawings

Lay-out	Base hold down	Terminals type
		