

WOLF VITALTECH 15W40

06/12/2023
14636

This is a high-performance mineral diesel engine oil formulated to deliver reliable performance in a broad range of heavy-duty applications. It is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines).

APPLICATIONS

Recommended for all modern diesel engines of trucks, off-road equipment and other heavy-duty applications. Universal use, including mixed fleets. Suitable for low-emission diesel engines with EGR (Euro II, III and some Euro IV). Meets and exceeds the demanding requirements of many U.S. and European diesel engine manufacturers.

FEATURES

Total engine protection: outstanding engine cleanliness and durability

SPECIFICATIONS

ACEA	A3/B4	DEUTZ	approval DQC-III-18
ACEA	E7	DEUTZ	DQC-III-10
API	approval CI-4/SL	GLOBAL	DHD-1
API	CF-4	IVECO	18-1804 Classe T2 E7
API	CG-4	MACK	approval EO-N
API	CH-4	MACK	EO-L
JASO	DH-1	MACK	EO-M PLUS
ALLISON	C4	MAN	M3275-1
CATERPILLAR	ECF-1a	MB	229.1
CATERPILLAR	ECF-2	MB	approval 228.3
CATERPILLAR	TO-2	MTU	approval Oil Category 2
CUMMINS	approval CES 20078	MTU	Oil Category 1
CUMMINS	CES 20076	RENAULT	approval RLD-2
CUMMINS	CES 20077	RENAULT	RLD
DAIMLER TRUCK	approval DTFR 15B110	VOLVO	approval VDS-3
DETROIT DIESEL	DFS 93K215		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.886
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	97
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.8
Viscosity index	ASTM D2270		144
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-36
CCS viscosity at -20°C	ASTM D5293	mPa.s	6500
Sulfated Ash	ASTM D874	Mass %	1.49
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

