

WOLF OFFICIALTECH 10W-30 UHPD MF

26/02/2024
15765

This oil for gas powered HD engines offers exceptional wear resistance. It is capable of maintaining its original composition thanks to its outstanding oxidation resistance, shear resistance and aeration control, giving it an increased drain interval compared to previous formulations.

APPLICATIONS

Both modern and older gas powered engines benefit from this heavy-duty engine oil for most OEMs, making it a perfect match for a wide range of engine types. It is capable of offering optimal protection to a range of Caterpillar, Mack, Renault, Volvo and other market-leading engines with or without after-treatment system, turbo- or supercharger. It is compatible with emission control technology EURO IV, V and VI for trucks; as well as stage IIIB, IV, V and Tier 4i, 4f for heavy-duty off-road.

FEATURES

Improved engine cleanliness: increased operating hours
High wear protection: increased engine lifespan
Increased oxidative stability: extended optimal oil performance

SPECIFICATIONS

ACEA	E11	DAF	PSQL 2.1 E LD
ACEA	E6-16	DAIMLER TRUCK	DTFR 13D110
ACEA	E7	DAIMLER TRUCK	DTFR 15B110
ACEA	E8	DAIMLER TRUCK	DTFR 15C100
ACEA	E9-16	DAIMLER TRUCK	DTFR 15C110
API	approval CK-4	DAIMLER TRUCK	DTFR 15C120
API	CI-4	DETROIT DIESEL	DFS 93K215
API	CI-4 Plus	DETROIT DIESEL	DFS 93K218
API	CJ-4	DETROIT DIESEL	DFS 93K222
JASO	DH-1	DEUTZ	DQC IV-10 LA
JASO	DH-2	DEUTZ	DQC-III-10 LA
ALLISON	C4	DEUTZ	DQC-III-18 LA
CATERPILLAR	ECF-1a	DEUTZ	DQC-IV-18 LA
CATERPILLAR	ECF-2	FORD	WSS-M2C171-F1
CATERPILLAR	ECF-3	IVECO	18-1804 Classe T2 E7
CATERPILLAR	TO-2	IVECO	18-1804 Classe TLS E9
CUMMINS	CES 20076	JD	JDQ-78X
CUMMINS	CES 20077	LIEBHERR	LH-00-ENG5C LA
CUMMINS	CES 20078	MACK	approval EO-S 4.5
CUMMINS	CES 20081	MACK	EO-M PLUS
CUMMINS	CES 20085	MACK	EO-N
CUMMINS	CES 20086	MACK	EO-N Premium Plus
CUMMINS	CES 20092	MACK	EO-O Premium Plus
CUMMINS	CES 20100	MAN	M3271-1
DAF	EXTENDED DRAIN	MAN	M3477
DAF	PSQL 2.1 E	MAN	M3575

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfub.com



MAN	M3775	RENAULT	RLD
MB	228.3	RENAULT	RLD-2
MB	228.31	RENAULT	RLD-4
MB	228.51	RENAULT	RXD
MB	228.52	SCANIA	LA
MB	235.28	VOITH	Retarder Oil Class B
MTU	Oil Category 2.1	VOLVO	approval VDS-4.5
MTU	Oil Category 3.1	VOLVO	VDS-3
RENAULT	approval RLD-3	VOLVO	VDS-4
RENAULT	RGD		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.862
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	76.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.0
Viscosity index	ASTM D2270		153
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	10.2
Pour point	ASTM D6892	°C	-42
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

