

WOLF VITALTECH 75W-80 MV PREMIUM

11/08/2023
2219

This is a high quality semi synthetic transmission oil, suitable for nearly all manual gearboxes of passenger cars. It is especially suitable as a replacement for specific OEM original oils and reduces the complexity and storage of gearbox oils. Tested under strict conditions, this oil satisfies the general performance requirements of most car makers and models.

APPLICATIONS

This oil is recommended for all hypoid transmissions and is also suitable for spiral bevel gears, worm wheels and most transaxles in all weather.

FEATURES

Frictional properties: very smooth gear shifting, no vibration.
Anti-wear protection: significantly extended transmission life.
Extended oil life: proven resistance to oil degradation.

PERFORMANCE

API	GL-4 +	NISSAN	999MP-MTF20P
BMW	83 22 0 140 516	NISSAN	MT-XZ
BMW	83220309031	PSA	9730 A2
BMW	MTF LT-2	PSA	9730 A8
FIAT	9.55550-MX3	PSA	B71 2330
FIAT	9.55550-MZ1	SUBARU	K0321-F0090
FORD	ESD-M2C186-A	TOYOTA	JWS 227
FORD	WSS-M2C200-D2	VOLVO	97308
GM	1940182	VOLVO	97309
GM	1940768	VOLVO	97310
HONDA	MTF 94	VW	G 052 171
HYUNDAI	02200-00130 TOD	VW	G 052 527
LAND ROVER	TYK500030	VW	G 052 726
MB	235.10	VW	G 055 538
MITSUBISHI	MZ312644		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	48.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.8
Viscosity index	ASTM D2270		164
Pour point	ASTM D6892	°C	-39
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	100000
Density at 15°C	ASTM D4052	g/ml	0.867
Flash Point COC	ASTM D92	°C	212

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

