

WOLF ANTIFREEZE EVO LL

07/12/2023
50054

High-performing coolant concentrate based on ethylene glycol with state-of-the-art PSi-OAT corrosion protection technology, for modern high performance engines. With the PSi-OAT technology, organic acids work together with mineral inhibitors for the best possible protection.
This G12 evo coolant concentrate can be used in G13, G12++, G12+, and G11 applications.

APPLICATIONS

This concentrate must be diluted with water before use. It may only be used in a concentration of at least 33 vol% to a maximum of 60 vol%. We recommend a mixing ratio of 50:50 (vol.%) with only demineralised or distilled water.
It offers long-term protection in VW TL 774 L (G12 evo) applications and many more OEM applications.

FEATURES

Total system protection: excellent heat transfer and dispersion.
Anti-corrosion properties: outstanding corrosion protection.
Antifreeze properties: superior cold temperature performance.

SPECIFICATIONS

2G	-	ATLAS	-
AFNOR	NF R 15-601	AUDI	-
ASTM	D1384	BMW	LC-18
ASTM	D3306	BMW	LC-87
ASTM	D4340	BMW	LC-97
ASTM	D4985	BUGATTI	-
ASTM	D6210	BYD	.
AUSTRALIEN STD	AS 2108-2004	CASE	JIC-501
BS	6580-2010	CASE	MAT 3624
CHINESE STANDARD	GB 29743	CATERPILLAR	GCM34
CUNA	NC 956-16	CHEVROLET	.
JIS	K2234:2018	CHRYSLER	.
KOREAN STD	KS M 2142	CITROËN	-
MIL	BT-PS-606 A	CLAAS	-
MIL	DCSEA 615/C	CUMMINS	85T8-2
MIL	E/L-1415b	CUMMINS	CES 14439
MIL	FS 6850-0951	CUMMINS	CES 14603
MIL	TL 6850-0038	DAEWOO	-
NATO	S759	DAF	MAT 74002
POLISH STANDARD	PN-C-40007	DAIHATSU	-
SAE	J1034	DAIMLER TRUCK	DTFR 29C100
SAE	J1941	DAIMLER TRUCK	DTFR 29C110
SAE	J814	DAIMLER TRUCK	DTFR 29D120
SANS	1251:2005	DEUTZ	DQC-CA-14
SWISS FED.LAB	EMPA 170'803	DEUTZ	DQC-CB-14
UNE	26-361-88/1	DEUTZ	DQC-CC-14
ALFA ROMEO	.	DEUTZ-FAHR	-
APRILIA	-	DODGE	.
ASTON MARTIN	.	DUCATI	-

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



EICHER ENGINES	-	MB	325.5
FAUN	-	MB	325.6
FENDT	-	MIL	FSD 8704
FERRARI	.	MINI	LC-87
Fiat	.	MITSUBISHI	.
FORD	.	MTU	MTL 5048
FORD	WSS-M97B44-D	MWM	-
FORD	WSS-M97B57-A1	NISSAN	-
FUSO	-	OPEL	.
FVV STD	FVV R 530:2005	OPEL	B 040 240
GILERA	-	OPEL	GME L1301
GM	B 040 1065	PERKINS	-
GM	GMW 3420	PIAGGIO	.
GMC	.	PORSCHE	-
HINO	-	PSA	-
HITACHI	-	RENAULT	-
HONDA	.	ROLLS-ROYCE	.
HUERLIMANN	-	ROLLS-ROYCE	LC-87
HYUNDAI	.	ROLLS-ROYCE	MTL 5048
IRISBUS	-	ROVER/MG	-
IRIZAR	-	SAAB	.
ISUZU	.	SAAB	690 1599
IVECO	18-1830	SAME	-
JAGUAR	.	SCANIA	-
JAGUAR	CMR 8229	SEAT	.
JAGUAR	E-VEHICLES	SETRA	-
JAGUAR-LAND ROVER	STJLR.651.5003	SKODA	.
JD	-	SMART	.
JEEP	-	STEYER MOTORS	-
JENBACHER	TA 1000-0200	SUBARU	.
KAWASAKI	-	SUZUKI	.
KIA	.	SYM	-
KOBELCO	-	TADANO	-
KOMATSU	-	TESLA	-
KTM	-	TGB	-
KYMCO	-	TOYOTA	.
LADA	.	TRIUMPH	-
LAMBORGHINI	-	VAN HOOL	-
LANCIA	.	VAUXHALL	GME L1301
LAND ROVER	.	VAUXHALL	GMW 3420
LAND ROVER	E-VEHICLES	VOLVO	TR-31854114-002
LAND ROVER	STJLR.651.5003	VW	TL 774-C (G11)
LEXUS	.	VW	TL 774-D (G12)
LIEBHERR	-	VW	TL 774-F (G12+)
LIEBHERR	LH-00-COL5C	VW	TL 774-G (G12++)
LOTUS	-	VW	TL 774-J (G13)
MAHLE	-	VW	TL 774-L (G12 EVO)
MAN	175D	YAMAHA	-
MAN	324 NF	YANMAR	-
MAN	324 Si-OAT		
MAN	324 Si-OAT EVO		
MAN	324 SNF		
MAZDA	.		
MB	325.0		
MB	325.3		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Freezing point 50% vol. AF	ASTM D1177	°C	-36
Reserve alkalinity	ASTM D1121	ml 0.1M HCl	10.5
Density at 20°C	ASTM D4052	g/ml	1.125
Colour	VISUAL		PINK

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

