

WOLF COOLANT EVO LL -36°C

07/12/2023
50154

High-performing ready-to-use coolant based on ethylene glycol with state-of-the-art PSi-OAT corrosion protection technology, for modern high performance engines. With the PSi-OAT technology, organic acids work together with mineral inhibitors for the best possible protection. This G12 evo coolant can be used in G13, G12++, G12+, and G11 applications.

APPLICATIONS

This PSi-OAT coolant is especially developed for the protection of modern combustion engines cooling systems made of aluminium and aluminium alloys. It is basically miscible with most OAT MEG based coolants but for the best possible corrosion protection we recommend to use only this PSi-OAT coolant. It offers long-term protection in VW TL 774 L (G12 evo) applications and many more OEM applications.

FEATURES

Total system protection: excellent heat transfer and dispersion.

Anti-corrosion properties: outstanding corrosion protection.

Antifreeze properties: superior cold temperature performance.

SPECIFICATIONS

2G	-	ATLAS	-
AFNOR	NF R 15-601	AUDI	-
ASTM	D1384	BENTLEY	-
ASTM	D3306	BMW	LC-18
ASTM	D4340	BMW	LC-87
ASTM	D4985	BMW	LC-97
ASTM	D6210	BUGATTI	-
AUSTRALIEN STD	AS 2108-2004	BYD	.
BS	6580-2010	CASE	JIC-501
CHINESE STANDARD	GB 29743	CASE	MAT 3624
CUNA	NC 956-16	CATERPILLAR	GCM34
JIS	K2234:2018	CHEVROLET	.
MIL	BT-PS-606 A	CHRYSLER	.
MIL	DCSEA 615/C	CITROËN	-
MIL	E/L-1415b	CLAAS	-
MIL	FS 6850-0951	CUMMINS	85T8-2
MIL	TL 6850-0038	CUMMINS	CES 14439
NATO	S759	CUMMINS	CES 14603
POLISH STANDARD	PN-C-40007	DACIA	.
SAE	J1034	DAEWOO	-
SAE	J1941	DAF	MAT 74002
SAE	J814	DAIHATSU	-
UNE	26-361-88/1	DAIMLER TRUCK	DTFR 29C100
ALFA ROMEO	.	DAIMLER TRUCK	DTFR 29C110
APRILIA	-	DAIMLER TRUCK	DTFR 29D120
ASTON MARTIN	.	DEUTZ	DQC-CA-14

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



DEUTZ	DQC-CB-14
DEUTZ	DQC-CC-14
DEUTZ-FAHR	-
DODGE	.
DUCATI	-
EICHER ENGINES	-
FAUN	-
FENDT	-
FERRARI	.
Fiat	.
FORD	.
FORD	WSS-M97B44-D
FORD	WSS-M97B57-A1
FUSO	-
FVV STD	FVV R 530:2005
GILERA	-
GM	B 040 1065
GM	GMW 3420
GMC	.
HITACHI	-
HONDA	.
HUERLIMANN	-
HYUNDAI	.
IRISBUS	-
IRIZAR	-
ISUZU	.
IVECO	18-1830
JAGUAR	.
JAGUAR	CMR 8229
JAGUAR	E-VEHICLES
JAGUAR-LAND ROVER	STJLR.651.5003
JD	-
JEEP	-
JENBACHER	TA 1000-0200
KAWASAKI	-
KIA	.
LADA	.
LANCIA	.
LAND ROVER	.
LAND ROVER	E-VEHICLES
LAND ROVER	STJLR.651.5003
LEXUS	.
LIEBHERR	-
LIEBHERR	LH-00-COL5C
MAN	175D
MAN	324 NF
MAN	324 Si-OAT
MAN	324 Si-OAT EVO
MAN	324 SNF
MAZDA	.
MB	326.5
MB	326.6
MIL	FSD 8704
MINI	LC-87
MITSUBISHI	.

MTU	MTL 5048
NISSAN	-
OPEL	.
OPEL	B 040 240
OPEL	GME L1301
PERKINS	-
PIAGGIO	.
PORSCHE	-
PSA	-
RENAULT	-
ROLLS-ROYCE	.
ROLLS-ROYCE	LC-87
ROLLS-ROYCE	MTL 5048
SAAB	.
SAAB	690 1599
SCANIA	-
SEAT	.
SKODA	.
SMART	.
SUBARU	.
SUZUKI	.
TESLA	-
TOYOTA	.
VAUXHALL	GMW 3420
VOLVO	TR-31854114-002
VW	TL 774-C (G11)
VW	TL 774-D (G12)
VW	TL 774-F (G12+)
VW	TL 774-G (G12++)
VW	TL 774-J (G13)
VW	TL 774-L (G12 EVO)

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
pH	ASTM D1287		8.10
Density at 20°C	ASTM D4052	g/ml	1.062
Colour	VISUAL		PINK
Freezing point (refracto)	ASTM D3321	°C	-36
Water content	ASTM D1123	% wt/wt	50

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

