

# WOLF OFFICIALTECH OW-20 UHPD DT-FE

29/10/2024  
65656

This full synthetic engine oil has been developed to offer high performance and ultimate protection of the latest Daimler Truck engines with a DTFR 15C140 engine oil specification. Its particular formulation gives this low SAPS engine oil extraordinary features.

## APPLICATIONS

This low SAPS engine oil meets and exceeds the newest DTFR 15C140 (former MB 229.71) engine oil specification in OW-20 viscosity grade.

## FEATURES

aftertreatment protection: full aftertreatment system protection  
fuel economy  
: superior fuel economy and CO2 reduction

total engine protection  
: outstanding engine cleanliness and durability

## SPECIFICATIONS

DAIMLER TRUCKS DTFR 15C140 MB 228.71

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	39
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	8.5
Viscosity index	ASTM D2270		167
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-45
Sulfated Ash	ASTM D874	Mass %	0.86
Flash Point COC	ASTM D92	°C	218

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

