

WOLF OE LEVELTECH 5W-30 UHPD

06/02/2024
75707

This synthetic based engine oil meets the specifications of a very broad range of different large truck manufacturers. Its low viscosity formulation and advanced friction modifiers allow you to increase fuel efficiency.

APPLICATIONS

This versatile lubricant can be used in a broad range of different EURO V and EURO VI engines. It meets the specifications of different off- and on-road engine manufacturers, such as: Caterpillar, Cummins, DAF, Daimler Truck, Iveco, MAN, Renault, Scania, Volvo, etc.

FEATURES

Low viscosity and excellent friction reduction: increased fuel efficiency
Broad applicability: can be used to service multiple vehicles within one fleet

SPECIFICATIONS

ACEA	E11	MACK	EO-N
ACEA	E6-16	MACK	EO-N Premium Plus
ACEA	E7	MACK	EO-O Premium Plus
ACEA	E9-16	MACK	EO-S 4.5
API	CI-4	MAN	M3271-1
API	CJ-4	MAN	M3277
API	CK-4	MAN	M3477
JASO	DH-2	MAN	M3677
CATERPILLAR	ECF-3	MB	228.31
CUMMINS	CES 20077	MB	228.5
CUMMINS	CES 20081	MB	228.51
CUMMINS	CES 20086	MB	228.52
DAF	EXTENDED DRAIN	MB	235.28
DAF	PSQL 2.1 E	MTU	Oil Category 2.1
DAF	PSQL 2.1 E LD	MTU	Oil Category 3
DAIMLER TRUCK	DTFR 13D110	MTU	Oil Category 3.1
DAIMLER TRUCK	DTFR 15C100	RENAULT	RGD
DAIMLER TRUCK	DTFR 15C110	RENAULT	RLD
DAIMLER TRUCK	DTFR 15C120	RENAULT	RLD-2
DETROIT DIESEL	DFS 93K218	RENAULT	RLD-3
DETROIT DIESEL	DFS 93K222	RENAULT	RLD-4
DEUTZ	DQC IV-10 LA	RENAULT	RXD
DEUTZ	DQC-IV-10	SCANIA	LDF-3 (excl. V8 engines)
DEUTZ	DQC-IV-18 LA	SCANIA	LDF-4
DEUTZ	TTCO	VOITH	Retarder Oil Class B
FORD	WSS-M2C213-A1	VOLVO	VDS-2
IVECO	18-1804 Classe TLS E9	VOLVO	VDS-4
MACK	EO-M PLUS	VOLVO	VDS-4.5

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	74.6
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.2
Viscosity index	ASTM D2270		161
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	11.9
Pour point	ASTM D6892	°C	-39
Sulfated Ash	ASTM D874	Mass %	0.99
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

