

CHAMPION **ECO FLOW** OW16 SP/RC G6 XFE

Thanks to its low viscosity and outstanding fluidity this oil significantly reduces wear and ensures fuel savings and lower CO2 emissions. Optimized additive package reduces soot and deposits and keeps the engine clean.

APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest ILSAC GF-6 B standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

FEATURES

Total engine protection: performance in keeping the engine clean.

Fuel economy: superior fuel economy and CO2 reduction.

Cold start: excellent fluidity at low temperature.

PERFORMANCE

API	approval SN Plus	ILSAC	approval GF-6 B
API	approval SP/RC	LEXUS	.
API	SN Plus/RC	TOYOTA	.
API	SP		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	34.8
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.9
Viscosity index	ASTM D2270		163
B.N. [HCL04 method]	ASTM D2896	mg KOH/g	8.5
Pour point	ASTM D6892	°C	-45
Density at 15°C	ASTM D4052	g/ml	0.846
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

