

# CHAMPION **ECO FLOW** 10W30 SP/RC G6 HC

This semi-synthetic oil significantly reduces wear and ensures fuel savings and lower CO2 emissions. Optimized additive package reduces soot and deposits and keeps the engine clean.

## APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest ILSAC GF-6 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

## FEATURES

Total engine protection: performance in keeping the engine clean.

Fuel economy: superior fuel economy and CO2 reduction.

Cold start: excellent fluidity at low temperature.

## SPECIFICATIONS

|     |                  |          |                 |
|-----|------------------|----------|-----------------|
| API | approval SN Plus | ILSAC    | approval GF-6 A |
| API | approval SP/RC   | ILSAC    | GF-5            |
| API | SN/RC            | CHRYSLER | MS 6395         |
| API | SP               | GM       | 6094M           |

## TYPICAL CHARACTERISTICS

| Test                         | Method     | Unit               | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C              | ASTM D4052 | g/ml               | 0.849           |
| Kinematic viscosity at 40°C  | ASTM D445  | mm <sup>2</sup> /s | 64.2            |
| Kinematic viscosity at 100°C | ASTM D445  | mm <sup>2</sup> /s | 10.6            |
| Viscosity index              | ASTM D2270 |                    | 155             |
| B.N. [HClO4 method]          | ASTM D2896 | mg KOH/g           | 7.4             |
| Pour point                   | ASTM D6892 | °C                 | -39             |
| Flash Point COC              | ASTM D92   | °C                 | 220             |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

