

CHAMPION OEM SPECIFIC

75W-85 FE LS GL 5

This premium, fully synthetic, transmission SAE 75W-85 limited slip [LS] oil is especially developed for manual transmissions and differentials [LS and non-LS]. The use of special friction modifiers reduces internal friction, thereby obtaining fuel economy [FE] properties.

APPLICATIONS

This fuel-saving, fully synthetic SAE 75W-85 transmission oil with Limited Slip properties has been specifically engineered for use in Mercedes Benz passenger car axles and other applications specified by MB 235.7, MB 235.74, MB 239.71 or MB 239.72.

Amongst many other applications also suitable for VAG Multitronic transmissions for which VW's TL 521 90 specification is required.

FEATURES

Low viscosity: fuel economy potential.

Frictional properties: easy gear shifting.

Excellent thermal stability: long gear and bearing life.

SPECIFICATIONS

API	GL-4	CHRYSLER	68237820AA
API	GL-5	CHRYSLER	68333589AA
API	MT-1	CHRYSLER	68378949AA
MIL	L-2105 D	CHRYSLER	ELSD REAR AXLE
MIL	L-2105 E	CHRYSLER	MS A0450
SAE	J 2360	DODGE	.
ACURA	08200-9014A	FIAT	9.55550,CTR F426.E06
ACURA	HYPPOID GEAR OIL HGO-1	FORD	WSS-M2C942-A
AISIN-WARNER	JWS 2273	FORD	XY-75W85-QL
BMW	83 12 0 445 838	GENESIS	.
BMW	83 22 2 239 982	GM	19300457
BMW	83 22 2 295 532	GM	1940012
BMW	83 22 2 413 511	GM	19418501
BMW	83 22 2 413 512	GM	88862826
BMW	83 22 2 447 362	GM	92184900
BMW	B0T 448	GM	93165290
BMW	HYPPOID AXLE OIL G1	GM	9986551
BMW	HYPPOID AXLE OIL G2	GM	SAF CARBON MOD
BMW	HYPPOID AXLE OIL G3	GM	SAF-EH MOD LV
BMW	HYPPOID AXLE OIL G4	GMC	.
CADILLAC	.	HONDA	08200-9014
CHRYSLER	05136035AA	INFINITI	KDL38-75801P
CHRYSLER	68083381AA	JAGUAR	.
CHRYSLER	68210057AA	JEEP	-
CHRYSLER	68218654AA	LAND ROVER	LR052059
CHRYSLER	68232948AA	LEXUS	08885-02506

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com



LEXUS	08885-02606	MOPAR	LL HYPOID GEAR OIL
LEXUS	08885-81060	NISSAN	KDL38-75801P
LEXUS	GEAR OIL LT/LX	TOYOTA	08885-02506
LINCOLN	.	TOYOTA	08885-02606
MAZDA	HYPOID GEAR OIL (SG1)	TOYOTA	08885-81060
MAZDA	K020-01-SG1	TOYOTA	08885-81081
MB	231.1	TOYOTA	GEAR OIL LT/LX
MB	235.15	TOYOTA	JWS 2273
MB	235.16	VOLVO	97312
MB	235.31	VW	G 052 190
MB	235.62	VW	G 052 196
MB	235.7	VW	G 052 513
MB	235.74	VW	G 055 190
MB	239.71	VW	G 060 190
MB	239.72	VW	TL 52 190
MB	A 000 989 73 04	ZF	TE-ML 02B
MB	A 000 989 88 03	ZF	TE-ML 08
MB	A 001 989 33 03	ZF	TE-ML 18
MB	A 001 989 59 03	ZF	TE-ML-12F
MB	A 002 989 02 03	ZF	TE-ML-19D
MG	.		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.863
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	53.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.4
Viscosity index	ASTM D2270		215
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	200

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

