

TECHNICAL DATA SHEET



Type no.		AGM 570 01
Article no.		016570010101
Standards		DIN EN 50342-1, 50342-2
Application		Starter battery start-stop
Electrical data		
Rated voltage		12V
Rated capacity		70 Ah (K20)
Cold start current		720 A (EN)
Dimensions and weights		
Box	H6	
Length max.	278mm	
Width max.	175mm	
Box height max.	190mm	
Total height max.	190mm	
Battery weight	Ca. 21,0 kg (+/- 5 %)	
Electrolyte density		Approx. 1,32 kg/l
Electrolyte		Diluted sulphuric acid
Items/pallet		64
Pallet ID		Euro pallet
Items per layer		16
Features		
Base hold-down		B13
Layout		0
Terminal		1
Separator		AGM separator
Degassing		Battery with central degassing
Flame arrester		Integrated
Performance identification		W5 - C2 - V3 - M3 (E4)
Maintenance ¹⁾		
Water consumption		W5
Refill water		Absolutely maintenance-free
Self-discharge		Approx. 3 % per month
Charging current		Approx. 1/20 of the rated capacity
Charging voltage ²⁾		max. 14,8 V

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2020-09-30 ; Rights relating to changes and errors retained.
original