

Prüfbericht 366-0514-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000817

ANLAGE: 9.5
 Hersteller: MW Aftermarket Srl

Radtyp: 14554098-3
 Stand: 21.10.2015



Seite: 1 von 1

Manufacturer : **FIAT**

Wheel dates:

Wheel size according to standard : 5 1/2 J X 14 H2 Off set(mm) : 37
 Hole circle (mm)/number of holes : 98/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1127	R1-1127	Without	58		635	1836	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **FIAT**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm

commercial type: **FIAT DOBLO,CARGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
223 L	K750	46 -77	175/70R14 88		1); 2); 33)
223 L	K750	55 -76	175/70R14 M+S		1); 2); 33)
		68 -76	175/70R14C 95		

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.