

**Prüfbericht 366-0515-15-WIRD/N1**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000822**

ANLAGE: 9.7

Hersteller: MW Aftermarket Srl

Radtyp: 14554100-15

Stand: 11.11.2015



Seite: 1 von 1

**Manufacturer : HONDA****Wheel dates:**

Wheel size according to standard : 5 1/2 J X 14 H2 Off set(mm) : 45

Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1148	R1-1148	Without	56		463	1880	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : HONDA**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 110 Nm

commercial type: **HONDA CIVIC**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
EP1	e11*98/14*0173*..	66	185/70R14-88H		1); 2); 33)
EP2	e11*98/14*0174*..	81	185/70R14-88H		1); 2); 33)
EP4	e11*98/14*0188*..	74	185/70R14-88H		1); 2); 33)
EU5	e11*98/14*0158*..	66	185/70R14		1); 2); 33)
EU6	e11*98/14*0159*..	81	185/70R14		1); 2); 33)
EU7	e11*98/14*0160*..	66	185/70R14		1); 2); 33)
EU8	e11*98/14*0161*..	81	185/70R14		1); 2); 33)

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.