

**Prüfbericht 366-0074-16-WIRD
zur Erteilung der ECE (E1) 124R- 001045**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 14605100-40

Stand: 25.02.2016



Seite: 1 von 2

Manufacturer : SEAT, SKODA, VOLKSWAGEN

Wheel dates:

Wheel size according to standard : 6 J X 14 H2

Off set(mm) : 38

Hole circle (mm)/number of holes : 100/5

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1273	R1-1273	Without	57		505	1940	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : SEAT

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: SEAT TOLEDO/LEON

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1M	e9*97/27*0026*..	50 -74	175/80R14		*) ; Front wheel drive; 1); 2); 33)
1M	e9*98/14*0026*..	50 -77	175/80R14		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : SKODA

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

commercial type: SKODA OCTAVIA

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1U	e11*2001/116*0066*..	55	175/80R14 88		1); 2); 33)
		75	175/80R14 88H		
1U	e11*2007/46*0011*..	55	175/80R14 88		1); 2); 33)
		75	175/80R14 88H		
1U	e11*95/54*0066*..	44 -92	175/80R14		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : VOLKSWAGEN

Mounting parts : spherical collar bolt M14x1,5, diameter 26 mm

Tightening torque for fixing parts : 120 Nm

Prüfbericht 366-0074-16-WIRD
zur Erteilung der ECE (E1) 124R- 001045

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 14605100-40

Stand: 25.02.2016



Seite: 2 von 2

commercial type: **GOLF / BORA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
1J	e1*2001/116*0071*..	50-55	175/80R14 88		*); Hatchback; Front wheel drive; 1); 2); 33)
		75-77	175/80R14 88H		
1J	e1*96/79*0071*..	50-74	175/80R14		*); GOLF; BORA(Limousine); Limousine; Front wheel drive; 1); 2); 33)
1J	e1*98/14*0071*..	50-77	175/80R14		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.