

Prüfbericht 366-0516-15-WIRD
zur Erteilung der ECE (E1) 124R- 000828

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 14554108-25

Stand: 27.08.2015



Seite: 1 von 3

Manufacturer : **CITROEN, PEUGEOT**

Wheel dates:

Wheel size according to standard : 5 1/2 J X 14 CH Off set(mm) : 24

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1278	R1-1278	Without	65		540	1836	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **CITROEN**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm

commercial type: **CITROEN BERLINGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
G*KFW	e2*2001/116*0275*..	48 -55	175/70R14 84		1); 2); 33)
		55	175/65R14C		
G*RHY*	e2*2001/116*0278*..	66	175/65R14C		1); 2); 33)
			175/70R14 84		
G*WJY	e2*2001/116*0277*..	51	175/70R14 84		1); 2); 33)
G*9HW*	e2*2001/116*0338*..	55	175/65R14C		1); 2); 33)
			175/70R14 84		
G*9HX*	e2*2001/116*0321*..	66	175/65R14C		1); 2); 33)
			175/70R14 84		
M 4	H419	43 -55	165/70R14		1); 2); 33)
		44 -66	175/65R14		
M 59 GL	L161	54 -55	175/65R14C 90		1); 2); 33)
M 59 GN	L159	48 -58	175/65R14C		1); 2); 33)
M*DJY*	e2*93/81*0059*..	50	175/65R14		1); 2); 33)
			175/70R14		
M*HDZ	e2*93/81*0057*..	44 -45	175/65R14		1); 2); 33)
M*HDZ	e2*98/14*0057*..	44	175/65R14		1); 2); 33)
M*HFX*	e2*98/14*0224*..	44	175/65R14 86		1); 2); 33)
			175/65R14C		
M*KFW*	e2*98/14*0225*..	55	175/65R14 86		1); 2); 33)
			175/65R14C		
			175/70R14 84		
			175/70R14-84H		
M*KFX	e2*93/81*0058*..	55	175/65R14		1); 2); 33)
			175/70R14		
M*KFX	e2*98/14*0058*..	55	175/65R14		1); 2); 33)
			175/70R14		
M*LFX	e2*93/81*0132*..	66	175/65R14		1); 2); 33)
			175/70R14		

Prüfbericht 366-0516-15-WIRD
zur Erteilung der ECE (E1) 124R- 000828

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 14554108-25

Stand: 27.08.2015



Seite: 2 von 3

commercial type: **CITROEN BERLINGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
M*LFX	e2*98/14*0132*..	66	175/65R14 175/70R14		1); 2); 33)
M*NFU*	e2*98/14*0226*..	80	175/65R14 86 175/70R14 M+S 175/70R14 84 175/70R14-84H		1); 2); 33)
M*RHY	e2*98/14*0201*..	66	175/65R14 M+S 175/65R14 86 175/65R14C 175/70R14 84 175/70R14-84H		1); 2); 33)
M*WJY*	e2*98/14*0227*..	51	175/65R14 86 175/70R14 84 175/70R14-84H		1); 2); 33)
M*WJZ	e2*93/81*0181*..	51	175/65R14 175/70R14		1); 2); 33)
M*WJZ	e2*98/14*0181*..	51	175/65R14 175/70R14		1); 2); 33)
M59	L080	44 -66	175/65R14C		1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm

commercial type: **PEUGEOT PARTNER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
G*KFW	e2*2001/116*0279*..	55	175/65R14 175/70R14 84		1); 2); 33)
G*RHY	e2*2001/116*0282*..	66	175/65R14C 175/70R14 84		1); 2); 33)
G*WJY	e2*2001/116*0281*..	51	175/65R14C 90 175/70R14 84		1); 2); 33)
G*9HW*	e2*2001/116*0337*..	55	175/65R14C 175/70R14 84		1); 2); 33)
G*9HX*	e2*2001/116*0322*..	66	175/65R14C 175/70R14 84		1); 2); 33)
M 59 GL	L162	53 -55	175/65R14C		1); 2); 33)
M 59 GN	L163	48 -55	175/65R14C		1); 2); 33)
M59	L083	44 -66	175/65R14C		1); 2); 33)
5	H420	43 -55 44 -66	165/70R14 175/65R14		1); 2); 33)
5*DJY*	e2*93/81*0062*..	50	175/65R14 175/70R14		1); 2); 33)
5*HDZ	e2*93/81*0060*..	44 -45	175/65R14		1); 2); 33)
5*HDZ	e2*98/14*0060*..	44	175/65R14		1); 2); 33)
5*HFX*	e2*98/14*0228*..	44	175/65R14		1); 2); 33)

Prüfbericht 366-0516-15-WIRD
zur Erteilung der ECE (E1) 124R- 000828

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 14554108-25

Stand: 27.08.2015



Seite: 3 von 3

commercial type: **PEUGEOT PARTNER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5*KFW	e2*98/14*0229*..	55	175/65R14 86		1); 2); 33)
			175/65R14C		
			175/70R14 84		
			175/70R14-84H		
5*KFX	e2*93/81*0061*..	55	175/65R14		1); 2); 33)
			175/70R14		
5*KFX	e2*98/14*0061*..	55	175/65R14		1); 2); 33)
			175/70R14		
5*LFX	e2*93/81*0133*..	66	175/65R14		1); 2); 33)
			175/70R14		
5*LFX	e2*98/14*0133*..	66	175/65R14		1); 2); 33)
			175/70R14		
5*NFU*	e2*98/14*0230*..	80	175/65R14 86		1); 2); 33)
			175/65R14C		
			175/70R14-84 M+S		
			175/70R14-84H		
5*RHY	e2*98/14*0202*..	66	175/65R14		1); 2); 33)
			175/70R14		
5*WJY*	e2*98/14*0231*..	51	175/65R14 86		1); 2); 33)
			175/65R14C		
			175/70R14-84 M+S		
			175/70R14-84H		
5*WJZ	e2*93/81*0182*..	51	175/65R14		1); 2); 33)
			175/70R14		
5*WJZ	e2*98/14*0182*..	51	175/65R14		1); 2); 33)
			175/70R14		

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.