

Prüfbericht 366-0515-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000822

ANLAGE: 9.8
 Hersteller: MW Aftermarket Srl

Radtyp: 14554100-15
 Stand: 11.11.2015



Seite: 1 von 2

Manufacturer : NISSAN, RENAULT

Wheel dates:

Wheel size according to standard : 5 1/2 J X 14 CH Off set(mm) : 36
 Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1304	R1-1304	Without	60		547	1842	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : NISSAN

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **NISSAN KUBISTAR**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F1	L195	42 -45	165/70R14 85		1); 2); 33)
		42 -60	165/75R14C M+S		
		42 -62	165/70R14C		
		45 -62	175/70R14-80		
		70	175/65R14 82		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **RENAULT KANGOO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions	
KC	e2*93/81*0164*..	40 -59	165/70R14		1); 2); 33)	
			165/75R14			
KC	e2*98/14*0164*..	40 -59	165/75R14C 93		1); 2); 33)	
			40 -60	165/75R14C 93		
			40 -62	165/70R14 85		
				165/70R14C 89		
			40 -70	165/70R14		
				165/70R14 85		
				175/65R14 82		
42 -62	175/70R14 88					
45 -70	175/65R14 86					

Prüfbericht 366-0515-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000822

ANLAGE: 9.8
 Hersteller: MW Aftermarket Srl

Radtyp: 14554100-15
 Stand: 11.11.2015



Seite: 2 von 2

commercial type: **RENAULT KANGOO RAPID**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
FC	H984	40 -59	165/70R14		1); 2); 33)
			165/75R14		
		70	175/65R14		
FCT	K558	40 -60	165/70R14		1); 2); 33)
			165/75R14		

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.