

Prüfbericht 366-0516-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000828

ANLAGE: 9.6

Hersteller: MW Aftermarket Srl

Radtyp: 14554108-25

Stand: 26.01.2016



Seite: 1 von 2

Manufacturer : FORD**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 14 CH Off set(mm) : 47,5

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1330	R1-1330	Without	63,35		505	1835	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : FORD

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **FOCUS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DAW	e13*97/27*0037*..	55-74	175/70R14		1); 2); 33)
		55-96	185/65R14		
		66-96	175/70R14		
		96	185/65R14		
DAX	e13*98/14D0057*..	85-86	185/65R14 M+S		1); 2); 33)
DAX	e13*98/14D0057*..	85	185/65R14		1); 2); 33)
DAX	e13*98/14*0057*..	83	185/65R14		1); 2); 33)
DBW	e13*97/27*0038*..	55-66	175/70R14		1); 2); 33)
		55-96	175/70R14		
			185/65R14		
DBX	e13*98/14D0058*..	85-86	185/65R14 86 M+S		1); 2); 33)
DBX	e13*98/14D0058*..	85	185/65R14		1); 2); 33)
DBX	e13*98/14*0058*..	83	185/65R14		1); 2); 33)
DFW	e13*97/27*0039*..	55-96	185/65R14		1); 2); 33)
		66-96	175/70R14		
DNW	e13*97/27*0040*..	55-96	175/70R14 M+S		1); 2); 33)
			185/65R14		
		96	185/65R14 M+S		
DNW	e13*97/27*0040*..	55-96	175/70R14		1); 2); 33)
			185/65R14		
			185/65R14		
DNX	e13*98/14D0056*..	86	185/65R14 M+S		1); 2); 33)
DNX	e13*98/14D0056*..	85-86	185/65R14 M+S		1); 2); 33)
DNX	e13*98/14D0056*..	85-86	185/65R14		1); 2); 33)
DNX	e13*98/14*0056*..	83	185/65R14		1); 2); 33)

Prüfbericht 366-0516-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000828

ANLAGE: 9.6
Hersteller: MW Aftermarket Srl

Radtyp: 14554108-25
Stand: 26.01.2016



Seite: 2 von 2

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.