

Prüfbericht 22-00175-CX-GBM-04
zur Erteilung der ECE (E1) 124R- 000831

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 17.05.2022



Auto Service

Seite: 1 von 2

Manufacturer : FORD**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2

Off set(mm) : 52,5

Hole circle (mm)/number of holes : 108/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1338	R1-1338	Without	63,35		505	1876	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : FORD

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 100 Nm

commercial type: **FIESTA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JC3	N070	50 - 74	195/50R15 78		1); 2); 33)

commercial type: **FOCUS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DAW	e13*97/27*0037*..	55 - 85	195/55R15		1); 2); 33)
		55 - 96	195/60R15		
DAX	e13*98/14D0057*..	86	195/60R15		1); 2); 33)
DAX	e13*98/14*0057*..	83	195/60R15		1); 2); 33)
DBW	e13*97/27*0038*..	55 - 85	195/55R15		1); 2); 33)
		66 - 96	195/60R15		
DBX	e13*98/14D0058*..	86	195/60R15		1); 2); 33)
DBX	e13*98/14*0058*..	83	195/60R15		1); 2); 33)
DFW	e13*97/27*0039*..	55 - 85	195/55R15		1); 2); 33)
		55 - 96	195/60R15		
DNW	e13*97/27*0040*..	55 - 85	195/55R15		1); 2); 33)
		66 - 96	195/60R15		
DNX	e13*98/14D0056*..	86	195/60R15		1); 2); 33)
DNX	e13*98/14*0056*..	83	195/60R15		1); 2); 33)

commercial type: **FORD FIESTA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JD3	e1*2001/116*0210*..	44 - 74	195/50R15 76		1); 2); 33)
			195/50R15 77		
		50 - 74	195/50R15 78		
		66 - 110	195/50R15 80		
		110	185/55R15		
			185/55R15 M+S		

Prüfbericht 22-00175-CX-GBM-04
zur Erteilung der ECE (E1) 124R- 000831

ANLAGE: 9.2
 Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29
 Stand: 17.05.2022



Auto Service

Seite: 2 von 2

commercial type: **FORD FIESTA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JD3	e1*2001/116*0210*..	44 - 59	195/50R15 77		1); 2); 33)
		50 - 74	195/50R15 78		
		55	195/50R15 76		
		66 - 110	185/55R15-80		
		110	185/55R15 M+S		
JH1	e1*98/14*0191*..	44 - 74	195/50R15 77		1); 2); 33)
		50	195/50R15 78		
		51 - 59	195/50R15 76		
		66	195/50R15 80		
JH1	e1*98/14*0191*..	44 - 74	195/50R15 76		1); 2); 33)
		50	195/50R15 78		
		66	195/50R15 80		
		74	195/50R15 77		

commercial type: **FORD FUSION**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JU2	e1*98/14*0194*..	50 - 74	185/60R15		*); FUSION; up to e1*98/14*0194*25; 1); 2); 33)
			195/60R15		

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.