

Prüfbericht 366-0550-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000854

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16506170-80

Stand: 02.02.2017



Seite: 1 von 1

Manufacturer : IVECO**Wheel dates:**

Wheel size according to standard : 5 J X 16 H Off set(mm) : 115

Hole circle (mm)/number of holes : 170/6 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1347	R1-1347	Without	130		975	2129	47/14
R1-1347.MWRO	R1-1347	Without	130		975	2129	41/16

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : IVECO

Mounting parts : Flachbundmuttern M20x

Tightening torque for fixing parts : 500 Nm

commercial type: **Daily 45C., 45-.,50C.,50-..**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
S3	K687	63 - 122	195/75R16		*) ; twin tyres; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.