

Prüfbericht 22-00175-CX-GBM-04
zur Erteilung der ECE (E1) 124R- 000831

ANLAGE: 9.3
 Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29
 Stand: 17.05.2022



Auto Service

Seite: 1 von 3

Manufacturer : CITROEN, PEUGEOT

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 27
 Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1372	R1-1372	Without	65		553	1937	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : CITROEN

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 90 Nm

commercial type: **CITROEN C2**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
J*KFU*	e2*2001/116*0344*..	65	185/55R15-82H		1); 2); 3)
J*KFV*	e2*2001/116*0284*..	54	185/55R15-82H		1); 2); 3)
J*NFU*	e2*2001/116*0285*..	80	185/55R15-82H		1); 2); 3)
J*8HX*	e2*2001/116*0286*..	50	185/55R15-82H		1); 2); 3)
J*8HZ*	e2*2001/116*0316*..	50	185/55R15-82H		1); 2); 3)

commercial type: **CITROEN C3**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
F*HFV*	e2*98/14*0256*..	44	185/60R15 84H		1); 2); 3)
F*KFU*	e2*2001/116*0289*..	65	185/60R15 84H		1); 2); 3)
F*KFV*	e2*98/14*0257*..	54	185/60R15 84H		1); 2); 3)
F*NFU*	e2*98/14*0258*..	80	185/60R15 84H		1); 2); 3)
F*8HX*	e2*98/14*0259*..	50	185/60R15 84H		1); 2); 3)
F*8HY*	e2*98/14*0261*..	66	185/60R15 84H		1); 2); 3)
F*8HZ*	e2*2001/116*0317*..	50	185/60R15 84H		1); 2); 3)
F*9HX*	e2*2001/116*0318*..	66	185/60R15 84H		1); 2); 3)
F*9HZ*	e2*2001/116*0329*..	80	185/60R15 84H		1); 2); 3)

commercial type: **CITROEN C3 PLURIEL**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
H	e2*2001/116*0266*..	50 - 80	185/65R15-88H		1); 2); 3)

commercial type: **CITROEN C4**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
L	e2*2001/116*0302*..	65 - 103	195/65R15 91H		1); 2); 3)
L*****	e2*2001/116*0302*..	65 - 103	195/65R15 91H		1); 2); 3)

Prüfbericht 22-00175-CX-GBM-04
zur Erteilung der ECE (E1) 124R- 000831

ANLAGE: 9.3
 Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29
 Stand: 17.05.2022



Auto Service

Seite: 2 von 3

Manufacturer : CITROEN, PEUGEOT

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 90 Nm

commercial type: **PEUGEOT 1007**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
K*****	e2*2001/116*0300*..	50 - 80	185/60R15 84H		1); 2); 3)

commercial type: **PEUGEOT 206**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
2*KFU*	e2*2001/116*0291*..	65	195/55R15 85H		1); 2); 3)
2*NFU*	e2*98/14*0238*..	80	185/55R15-82V 195/55R15 85H		1); 2); 3)
2*RFK*	e2*2001/116*0269*..	130	195/55R15 82V		1); 2); 3)
2*RFN*	e2*98/14*0239*..	100	195/55R15		*) ; Station wagon; 1); 2); 3)
2*RFN*	e2*98/14*0239*..	100	185/55R15-82V 195/55R15 85H		1); 2); 3)
2*RHY	e2*98/14*0174*..	66	195/55R15		*) ; Station wagon; 1); 2); 3)
2*RHY	e2*98/14*0174*..	66	185/55R15 195/55R15		*) ; Limousine; 1); 2); 3)
2*9HY*	e2*2001/116*0343*..	80	195/55R15 85H		1); 2); 3)
2*9HZ*	e2*2001/116*0310*..	80	195/55R15 85H		1); 2); 3)

commercial type: **PEUGEOT 206+**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
2	e2*2001/116*0374*..	50 - 55	185/60R15 84H		1); 2); 3)
2*****	e2*2001/116*0374*..				

commercial type: **PEUGEOT 307**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
3*KFU*	e2*2001/116*0288*..	65	195/65R15 91 195/65R15 91H		1); 2); 3)
3*KFU*	e2*2001/116*0288*..	65	195/65R15 91 195/65R15 91H		1); 2); 3)
3*KFW*	e2*98/14*0242*..	55	195/65R15		1); 2); 3)
3*NFU*	e2*2001/116*0243*..	80	195/65R15 91 195/65R15 91H		1); 2); 3)
3*NFU*	e2*98/14*0243*..	80	195/65R15 91		1); 2); 3)
3*RHY*	e2*98/14*0245*..	66	195/65R15		1); 2); 3)
3*8HZ*	e2*98/14*0251*..	50	195/65R15		1); 2); 3)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

**Prüfbericht 22-00175-CX-GBM-04
zur Erteilung der ECE (E1) 124R- 000831**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 15604108-29

Stand: 17.05.2022



Auto Service

Seite: 3 von 3

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 3) Only for vehicles from date of manufacture 04.2000.