

**Prüfbericht 366-0525-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000823**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15554100-16

Stand: 15.04.2015



Seite: 1 von 1

**Manufacturer : RENAULT****Wheel dates:**

Wheel size according to standard : 5 1/2 J X 15 H2 Off set(mm) : 43

Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1433	R1-1433	Without	60		515	1895	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : RENAULT**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 100 Nm

commercial type: **RENAULT KANGOO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
KC	e2*98/14*0164*..	59 -70	185/65R15		*); all-wheel drive; 1); 2); 33)
			185/65R15 92		
		62 -70	185/65R15 88 M+S		

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.