

**Prüfbericht 366-0525-15-WIRD/N1**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000823**

**ANLAGE: 9.5**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15554100-16  
 Stand: 26.08.2015



Seite: 1 von 1

**Manufacturer : NISSAN**

**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 15 H2      Off set(mm) : 50  
 Hole circle (mm)/number of holes : 100/4      centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1435	R1-1435	Without	60		451	1857	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : NISSAN**

Mounting parts : conical collar nut M12x1,25, tapered thread 60 Grad, for Type : K13  
 Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : K12  
 Accessories : Serie  
 Tightening torque for fixing parts : 100 Nm for Type : K13  
 113 Nm for Type : K12

commercial type: **NISSAN MICRA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
K12	e11*2001/116*0195*..	48 -60	175/65R15 81		1); 2); 33)
		48 -65	175/60R15 81		
		48 -81	175/60R15		
		63 -81	175/65R15 80		
K13	e13*2007/46*1111*..	59 -72	175/60R15 81H		1); 2); 33)

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.