

Prüfbericht 366-0516-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000828

ANLAGE: 9.7
 Hersteller: MW Aftermarket Srl

Radtyp: 14554108-25
 Stand: 26.01.2016



Seite: 1 von 2

Manufacturer : FORD, MAZDA

Wheel dates:

Wheel size according to standard : 5 1/2 J X 14 H2 Off set(mm) : 47,5
 Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1464	R1-1464	Without	63,35		440	1781	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : FORD

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **FORD FIESTA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions	
JD3	e1*2001/116*0210*..	44 -74	175/65R14		1); 2); 33)	
			175/65R14 M+S			
			175/65R14-77			
		50 -74	175/65R14-78			
		66	175/65R14-80			
JD3	e1*2001/116*0210*..	44 -59	175/65R14-77		1); 2); 33)	
			44 -74	175/65R14 M+S		
			50 -74	175/65R14-78		
		55	175/65R14 76			
		66	175/65R14-80			
JH1	e1*98/14*0191*..	43 -74	175/65R14 M+S		1); 2); 33)	
			175/65R14 76			
		50	175/65R14-78			
			175/65R14-80			
JH1	e1*98/14*0191*..	43 -74	175/65R14 M+S		1); 2); 33)	
			175/65R14-77			
		50	175/65R14-78			
			51 -59	175/65R14 76		
66	175/65R14-80					

commercial type: **FORD FUSION**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JU2	e1*98/14*0194*..	50 -74	185/60R14		*) ; ; up to e1*98/14*0194*25; 1); 2); 33)
JU2	e1*98/14*0194*..	50 -74	185/60R14 M+S		*) ; ; up to e1*98/14*0194*25; 1); 2); 33)

Prüfbericht 366-0516-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000828

ANLAGE: 9.7
 Hersteller: MW Aftermarket Srl

Radtyp: 14554108-25
 Stand: 26.01.2016



Seite: 2 von 2

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : MAZDA

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **MAZDA 2**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DY	e1*2001/116*0212*..	50 -74	175/65R14 82		1); 2); 33)
			175/65R14-82		
			M+S		
			175/65R14-82H		

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.