

**Prüfbericht 366-0574-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000836**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16705098-38

Stand: 30.06.2015



Seite: 1 von 2

**Manufacturer** : **CITROEN, FIAT, PEUGEOT**

**Wheel dates:**

Wheel size according to standard : 7 J X 16 H2

Off set(mm) : 27

Hole circle (mm)/number of holes : 98/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1470	R1-1470	Without	58		685	2025	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : **CITROEN**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad, for Type : E\*\*\*\*\*

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad, for Type : E

Tightening torque for fixing parts : 100 Nm

commercial type: **CITROEN C8**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*2007/46*0119*..	100	215/60R16 95H		1); 2); 33)
E*****	e2*98/14*0254*..	79 - 150	215/60R16 95H		1); 2); 33)
			215/60R16 99H		
			215/60R16 99V		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : **FIAT**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 100 Nm

commercial type: **FIAT ULYSSE, LANCIA PHEDRA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
179	e2*98/14*0255*..	79 - 150	215/60R16 95H		1); 2); 33)
			215/60R16 99H		
			88 - 125	215/60R16 99V	

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Prüfbericht 366-0574-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000836**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16705098-38

Stand: 30.06.2015



Seite: 2 von 2

**Scope/Vehicle Manufacturer : PEUGEOT**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,  
for Type : E; E\*\*\*\*\*

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,  
for Type : E\*\*\*\*\*, E

Tightening torque for fixing parts : 100 Nm

commercial type: **PEUGEOT 807**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
E	e2*98/14*0253*..	79 -150	215/60R16 95H		1); 2); 33)
E*****	e2*98/14*0253*..		215/60R16 95V		
			215/60R16 99H		

### Restrictions

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.