

Prüfbericht 366-0531-15-WIRD/N2
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827

ANLAGE: 9.9
 Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23
 Stand: 19.01.2016



Seite: 1 von 2

Manufacturer : OPEL, OPEL / VAUXHALL

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 43
 Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1478	R1-1478	Without	56,6		503	1840	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : OPEL, OPEL / VAUXHALL

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : X01Monocab; X-C/ROADSTER

Accessories : Serie

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : GMIC

Tightening torque for fixing parts : 110 Nm

commercial type: **MERIVA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
GMIC	e50*2001/116*0002*..	66	185/60R15		1); 2); 33)
GMIC	e50*2001/116*0002*..	65-77	185/60R15 84H		1); 2); 33)
		72-77	185/60R15 88H		

commercial type: **MERIVA-A**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
X01Monocab	e1*2001/116*0215*..	51-77	185/60R15 88		1); 2); 33)
		64-77	185/60R15 84		
		92	185/60R15 88H		

commercial type: **TIGRA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
X-C/ROADSTER	e11*2001/116*0227*..	51-92	185/55R15-82H		1); 2); 33)

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.

Prüfbericht 366-0531-15-WIRD/N2
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000827

ANLAGE: 9.9
Hersteller: MW Aftermarket Srl

Radtyp: 15604100-23
Stand: 19.01.2016



Seite: 2 von 2

- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.