

**Prüfbericht 21-00028-CX-GBM-06**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41

Stand: 29.09.2022



Auto Service

Seite: 1 von 3

**Manufacturer** : SKODA**Wheel dates:**

Wheel size according to standard : 6 J X 15 H2

Off set(mm) : 43

Hole circle (mm)/number of holes : 100/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1519	R1-1519	Without	57		500	1839	30/22

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : SKODAMounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,  
for Type : 6Y; 5J

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad, for Type : 5J

Tightening torque for fixing parts : 120 Nm

commercial type: **FABIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions	
5J	e8*2007/46*0319*..	44 - 92	195/55R15 M+S		744; 77E; 1); 2); 33)	
6Y	e11*98/14*0123*..	37 - 59	185/55R15-81		1); 2); 33)	
			195/50R15 82			
			37 - 85	195/50R15-82V		
			40 - 85	185/55R15-81H		
				195/50R15-82H		
			85	185/55R15-82H		
96	185/55R15 83H					

commercial type: **FABIA PRAKTIK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6Y	L164	47 - 51	185/55R15-81		1); 2); 33)
			195/50R15 82		

commercial type: **PRAKTIK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5J	N083	51 - 63	185/55R15 M+S		1); 2); 33)
			195/55R15		

**Prüfbericht 21-00028-CX-GBM-06**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837**

**ANLAGE: 9.2**  
 Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41  
 Stand: 29.09.2022



Auto Service

Seite: 2 von 3

commercial type: **ROOMSTER, FABIA, PRAKTIK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5J	e11*2001/116*0291*..	44 - 77	195/55R15 85H		*); from e11*2001/116*0291*26; 1); 2); 33)
		44 - 132	185/55R15 M+S	Fabia Hatchback; Fabia station wagon	
			185/55R15 M+S	ECO	
			185/55R15 M+S	Roomster, Praktik; ECO	
			185/55R15 M+S		
		51 - 77	185/60R15 84		
		55	185/60R15 84	ECO	
185/60R15 84					
77	185/60R15 84H				
5J	e11*2001/116*0291*..	44 - 77	185/55R15-81T M+S		*); only to e11*2001/116*0291*25; 1); 2); 33)
			195/55R15 85H		
		47 - 77	185/55R15 85 M+S		
			185/55R15 86 M+S		
		51 - 66	185/60R15 84		
77	185/60R15 84H				
5J	e11*2007/46*0013*..	44 - 66	185/55R15 81 M+S		*); From e11*2007/46*0013*04; 744; 1); 2); 33)
			185/55R15 82 M+S		
		44 - 77	195/55R15 85H		
			51 - 77	185/55R15 85 M+S	
		185/60R15 84			
		55	185/55R15 82 M+S		
			185/60R15 84		
77	185/60R15 84H				
5J	e11*2007/46*0013*..	44 - 77	185/55R15 81 M+S		744; 1); 2); 33)
			195/55R15 85H		
		51 - 77	185/55R15 85 M+S		
			59	185/60R15 84	
		63	185/55R15 86 M+S		

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

#### Restrictions

744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.

**Prüfbericht 21-00028-CX-GBM-06**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837**

**ANLAGE: 9.2**

Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41

Stand: 29.09.2022



Auto Service

Seite: 3 von 3

- 77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.
- 1) To be kept:
    - the standard wheel size and offset.
    - tyre size with service description (load and speed index) and tyre brand commitments
    - as well as limitations to snow tyres (M+S) from the car documents.
    - requirements and limitations of snow chains from the operating licence and the operation manual.
  - 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
  - 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.