

**Prüfbericht 20-00295-CX-GBM-06**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840**

**ANLAGE: 9.2**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45  
 Stand: 02.08.2023



Auto Service

Seite: 1 von 2

**Manufacturer** : **VOLVO**

**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 52,5  
 Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1577	R1-1577	Without	63,35		550	1989	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : **VOLVO**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad, for Type : M-2D; M  
 Accessories : Serie  
 Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad, for Type : M  
 Tightening torque for fixing parts : 90 Nm for Type : M-2D  
 110 Nm for Type : M

commercial type: **C30**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
M-2D	e1*2001/116*0427*..	74 - 162	195/60R16 205/55R16		1); 2); 33)

commercial type: **VOLVO S40, V50, C70, C30,V40**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
M	e4*2001/116*0076*..	74 - 169	195/60R16 205/55R16		1); 2); 33)
M	e4*2001/116*0076*..	84 - 187	205/55R16		*) ; VOLVO V40; VOLVO V40 CrossCountry; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.

**Prüfbericht 20-00295-CX-GBM-06**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840**

**ANLAGE: 9.2**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 02.08.2023



Auto Service

Seite: 2 von 2

- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.