

Prüfbericht 366-0525-15-WIRD/N1
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000823

ANLAGE: 9.6

Hersteller: MW Aftermarket Srl

Radtyp: 15554100-16

Stand: 26.08.2015



Seite: 1 von 1

Manufacturer : RENAULT**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 15 H2 Off set(mm) : 43

Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1579	R1-1579	Without	60		470	1840	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : RENAULT

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 110 Nm

commercial type: **CLIO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
R	e2*2001/116*0327*..	48 -58	165/65R15 81	Hatchback	1); 2); 33)
		55 -58	165/65R15 81	Only station wagon (Grandtour)	
R	e2*2007/46*0008*..	55	165/65R15 81		1); 2); 33)
			165/65R15 81 M+S		

commercial type: **MODUS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P	e2*2001/116*0319*..	48 -58	165/65R15 81	Modus (short axle)	1); 2); 33)
			185/60R15 88 M+S	Modus (short axle)	
			55 -58	165/65R15 81	
P	e2*2001/116*0319*..	48 -58	165/65R15 81		1); 2); 33)
			185/60R15 88		
P	e2*2007/46*0007*..	55	165/65R15 81		1); 2); 33)

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.