

Prüfbericht 20-00266-CX-GBM-05
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000830

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28

Stand: 06.05.2022



Auto Service

Seite: 1 von 2

Manufacturer : PEUGEOT**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 31
 Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1582	R1-1582	Without	65		553	1930	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : PEUGEOT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
 for Type : 3*8HZ*; 3*9HZ*; 3*RHR*; 3*RFN*; 3*NFU*; 3*RHS*;
 3*RHY*; 3*RFK*

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type :
 3*NFU*; 3*9HX*; 3*9HY*; 3*RFJ*; 3*9HV*

Tightening torque for fixing parts : 90 Nm

commercial type: **PEUGEOT 307**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
3*NFU*	e2*2001/116*0243*..	80	205/55R16 91V		1); 2); 33)
3*NFU*	e2*98/14*0243*..	80	205/55R16 91V		1); 2); 33)
3*RFJ*	e2*2001/116*0313*..	103	205/55R16 91V		1); 2); 33)
3*RFK*	e2*2001/116*0290*..	130	205/55R16 91V		1); 2); 33)
3*RFN*	e2*98/14*0244*..	100	205/55R16 91V		1); 2); 33)
3*RHR*	e2*2001/116*0235*..	100	205/55R16 91V		1); 2); 33)
3*RHS*	e2*98/14*0252*..	79	205/55R16		1); 2); 33)
3*RHY*	e2*98/14*0245*..	66	205/55R16		1); 2); 33)
3*8HZ*	e2*98/14*0251*..	50	205/55R16		1); 2); 33)
3*9HV*	e2*2001/116*0333*..	66	205/55R16 91V		1); 2); 33)
3*9HX*	e2*2001/116*0301*..	66	205/55R16 91V		1); 2); 33)
3*9HY*	e2*2001/116*0299*..	80	205/55R16 91V		1); 2); 33)
3*9HZ*	e2*2001/116*0287*..	80	205/55R16 91V		1); 2); 33)

Restrictions

- To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- Only permissible at vehicle models, which are allowed to use steel wheels as standard.

Prüfbericht 20-00266-CX-GBM-05
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000830

ANLAGE: 9.1
Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28
Stand: 06.05.2022



Auto Service

-
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.

Seite: 2 von 2