

Prüfbericht 20-00266-CX-GBM-05
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000830

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28

Stand: 06.05.2022



Auto Service

Seite: 1 von 2

Manufacturer : **CITROEN****Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 26

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

Technical dates, short form

| version | Version name | | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|---------|----------------------|--------------------------|------------------------|--------------------|--------------------------------|---|-------------------------------|
| | Wheel identification | Centering identification | | | | | |
| R1-1589 | R1-1589 | Without | 65 | | 600 | 1960 | 47/14 |

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : **CITROEN**

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
 for Type : R*RHR*; R*XFU*; R*9HZ*; L*****; R*4HP*; R*6FZ*;
 R*RHL*; R*6FY*; R*4HX*; R*4HS*; R*4HT*; R*4HR*; R*RFJ*; R*9HY*

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : L

Tightening torque for fixing parts : 90 Nm

commercial type: **CITROEN C4**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|----------|---------------|-----------------------|--------------|
| L | e2*2001/116*0302*.. | 65 - 130 | 205/55R16 90V | | 1); 2); 33) |
| | | | 205/55R16 91V | | |
| | | | 205/55R16 94V | | |
| | | 80 - 103 | 215/55R16 93V | | |
| L***** | e2*2001/116*0302*.. | 65 - 130 | 205/55R16 90V | | 1); 2); 33) |
| | | | 205/55R16 91V | | |
| | | | 205/55R16 94V | | |
| | | | 215/55R16 93V | | |

commercial type: **CITROEN C5**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|-----|---------------|-----------------------|--------------|
| R*RFJ* | e2*2001/116*0304*.. | 103 | 215/55R16 93W | | 1); 2); 33) |
| R*RHL* | e2*2001/116*0315*.. | 93 | 215/55R16 93W | | 1); 2); 33) |
| R*RHR* | e2*2001/116*0306*.. | 100 | 215/55R16 93W | | 1); 2); 33) |
| R*XFU* | e2*2001/116*0308*.. | 152 | 215/55R16 93W | | 1); 2); 33) |
| | | | 215/55R16 97W | | |
| R*4HP* | e2*2001/116*0348*.. | 120 | 215/55R16 93W | | 1); 2); 33) |
| | | | 215/55R16 97W | | |
| R*4HR* | e2*2001/116*0354*.. | 120 | 215/55R16 93W | | 1); 2); 33) |
| | | | 215/55R16 97W | | |
| R*4HS* | e2*2001/116*0353*.. | 125 | 215/55R16 93W | | 1); 2); 33) |
| | | | 215/55R16 97W | | |
| R*4HT* | e2*2001/116*0347*.. | 125 | 215/55R16 93W | | 1); 2); 33) |
| | | | 215/55R16 97W | | |
| R*4HX* | e2*2001/116*0307*.. | 98 | 215/55R16 93W | | 1); 2); 33) |

Prüfbericht 20-00266-CX-GBM-05
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000830

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 16654108-28

Stand: 06.05.2022



Auto Service

Seite: 2 von 2

commercial type: **CITROEN C5**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|----|---------------|-----------------------|--------------|
| R*6FY* | e2*2001/116*0334*.. | 92 | 215/55R16 93W | | 1); 2); 33) |
| R*6FZ* | e2*2001/116*0303*.. | 85 | 215/55R16 93W | | 1); 2); 33) |
| R*9HY* | e2*2001/116*0335*.. | 80 | 215/55R16 93W | | 1); 2); 33) |
| R*9HZ* | e2*2001/116*0305*.. | 80 | 215/55R16 93W | | 1); 2); 33) |

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.