

**Prüfbericht 366-0214-16-WIRD  
zur Erteilung der ECE (E1) 124R- 001168**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16705110-90

Stand: 10.05.2016



Seite: 1 von 1

**Manufacturer** : FIAT**Wheel dates:**

Wheel size according to standard : 7 J X 16 H2

Off set(mm) : 34

Hole circle (mm)/number of holes : 110/5

centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1594	R1-1594	Without	65		650	1958	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : FIAT

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 110 Nm

commercial type: **Alfa 159, Brera, Spider, Sportwagon**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
939	e3*2001/116*0212*..	85-125	205/55R16 91V		*); Alfa 159 (Limousine); Alfa 159 Sportwagon (station wagon); 1); 2); 33)
		85-136	215/55R16 93V		
		136	215/55R16 93W		

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.