

Prüfbericht 22-00097-CX-GBM-02
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001058

ANLAGE: 9.4

Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18

Stand: 17.07.2023



Auto Service

Seite: 1 von 2

Manufacturer : OPEL / VAUXHALL, SUZUKI**Wheel dates:**

Wheel size according to standard : 5 J X 14 CH

Off set(mm) : 45

Hole circle (mm)/number of holes : 100/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1596	R1-1596	Without	54		415	1795	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : OPEL / VAUXHALL

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 110 Nm

commercial type: **AGILA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
GMIA	e50*2001/116*0010*..	48 - 63	165/70R14 81		*) Front wheel drive; 1); 2); 33)
H-B	e4*2001/116*0135*..	48 - 69	165/70R14 81		*) Front wheel drive; 1); 2); 33)

Manufacturer : OPEL / VAUXHALL, SUZUKI

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : SUZUKIMounting parts : conical collar nut M12x1,25, tapered thread 60 Grad,
for Type : EZMounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad,
for Type : MZ; EX

Tightening torque for fixing parts : 85 Nm

commercial type: **SPLASH**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
EX	e4*2001/116*0130*..	48 - 69	165/70R14 81		1); 2); 33)
EX	e4*2007/46*0283*..	66 - 69	165/70R14 81		1); 2); 33)

commercial type: **SUZUKI SWIFT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
EZ	e4*2001/116*0102*..	68 - 75	165/70R14 81		1); 2); 33)
MZ	e4*2001/116*0090*..	51 - 75	165/70R14 81		1); 2); 33)

Prüfbericht 22-00097-CX-GBM-02**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001058****ANLAGE: 9.4**

Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18

Stand: 17.07.2023



Auto Service

Seite: 2 von 2

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.