

**Prüfbericht 366-0525-15-WIRD
zur Erteilung der ECE (E1) 124R- 000823**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 15554100-16

Stand: 15.04.2015



Seite: 1 von 1

Manufacturer : TOYOTA**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 15 CH Off set(mm) : 45

Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1607	R1-1607	Without	54		448	1840	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : TOYOTA

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 103 Nm for Type : XP9(a); XP9F(a)
110 Nm for Type : P1commercial type: **TOYOTA YARIS**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
P1	e6*2001/116*0064*..	77	185/55R15-81V		1); 2); 33)
P1	e6*98/14*0064*..	77 -78	185/55R15-81V		*) ; 3-türig; 5-türig; Front wheel drive; 1); 2); 33)

commercial type: **Toyota Yaris, Daihatsu Charade**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
XP9(a)	e11*2001/116*0248*..	51 -98	185/60R15 84H		1); 2); 33)
XP9F(a)	e11*2001/116*0249*..	51 -74	185/60R15 84H		1); 2); 33)
XP9F(a)	e11*2001/116*0249*..	51 -66	185/60R15 84H		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.