

**Prüfbericht 21-00319-CX-GBM-07**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000847**

**ANLAGE: 9.1**  
 Hersteller: MW Aftermarket Srl

Radtyp: 16655114-62  
 Stand: 21.04.2022



Auto Service

Seite: 1 von 1

**Manufacturer : HONDA**

**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 55  
 Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

**Technical dates, short form**

| version | Version name         |                          | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|---------|----------------------|--------------------------|---------------------|--------------------|-----------------------------|--|----------------------------|
|         | Wheel identification | Centering identification |                     |                    |                             |  |                            |
| R1-1610 | R1-1610              | Without                  | 64                  |                    | 543                         | 1928                                   | 47/14                      |

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : HONDA**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad  
 Tightening torque for fixing parts : 108 Nm

commercial type: **CIVIC 5DR, CIVIC TOURER**

| Vehicle type | Approval             | kW      | Tires         | Restrictions of tires | Restrictions                                   |
|--------------|----------------------|---------|---------------|-----------------------|--|
| FK1          | e11*2001/116*0255*.. | 61 - 73 | 205/55R16 91H |                       | *) ; only to e11*2001/116*0255*06; 1); 2); 33) |
| FK2          | e11*2001/116*0256*.. | 103     | 205/55R16     |                       | *) ; only to e11*2001/116*0256*06; 1); 2); 33) |
| FK3          | e11*2001/116*0257*.. | 103     | 205/55R16 91V |                       | *) ; only to e11*2001/116*0257*05; 1); 2); 33) |

commercial type: **HONDA CIVIC 3DR**

| Vehicle type | Approval             | kW  | Tires         | Restrictions of tires | Restrictions |
|--------------|----------------------|-----|---------------|-----------------------|--------------|
| FN1          | e11*2001/116*0297*.. | 103 | 205/55R16 91V |                       | 1); 2); 33)  |
| FN3          | e11*2001/116*0298*.. | 103 | 205/55R16 91V |                       | 1); 2); 33)  |

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.