

**Prüfbericht 366-0514-15-WIRD
zur Erteilung der ECE (E1) 124R- 000817**

ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 14554098-3

Stand: 14.04.2015



Seite: 1 von 1

Manufacturer : FIAT**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 14 H2 Off set(mm) : 32

Hole circle (mm)/number of holes : 98/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1628	R1-1628	Without	58		675	1885	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 90 Nm

commercial type: **FIAT DOBLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
223	e3*98/14*0071*..	68-76	175/70R14 88		1); 2); 3)
			175/70R14C		

commercial type: **FIAT DOBLO,CARGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
223 L	K750	55-76	175/70R14		1); 2); 3)
			175/70R14 M+S		
			175/70R14C 95		
			175/75R14C 99		

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 3) Only for vehicles from date of manufacture 04.2000.