

Prüfbericht 20-00295-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840

ANLAGE: 9.3
 Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45
 Stand: 02.08.2023



Auto Service

Seite: 1 von 2

Manufacturer : FORD, LAND ROVER (GB)

Wheel dates:

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 50
 Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1645	R1-1645	Without	63,35		705	2220	20/17

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : FORD

Mounting parts : conical collar nut M14x1,5, tapered thread 60 Grad
 Tightening torque for fixing parts : 133 Nm

commercial type: **GALAXY, S-MAX**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
WA6	e13*2001/116*0185*..	74 - 149	215/60R16	12K; 51G	*) ; Ford Galaxy; up to e13*2001/116*0185*23; 1); 2); 33)
WA6	e13*2001/116*0185*..	74 - 176	215/60R16	12K; 51G	*) ; Ford S-MAX; up to e13*2001/116*0185*23; 1); 2); 33)

Manufacturer : FORD, LAND ROVER (GB)

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : LAND ROVER (GB)

Mounting parts : conical collar nut M14x1,5, tapered thread 60 Grad
 Tightening torque for fixing parts : 133 Nm

commercial type: **FREELANDER 2**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
LF	e11*2001/116*0300*..	110	215/75R16 103		*) ; Front wheel drive; 1); 2); 33)
LF	e11*2001/116*0300*..	110 - 118	215/75R16	12K; 51G	*) ; All-wheel drive; Front wheel drive; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Prüfbericht 20-00295-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840**ANLAGE: 9.3**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 02.08.2023



Auto Service

Seite: 2 von 2

Restrictions

- 12K) The use of snow chains is only permitted if the latter have been approved by the vehicle manufacturer for this wheel/tire combination (cf. operating instructions).
- 51G) This wheel/tire combination may only be used if this tire has already been entered as the standard in vehicle documents or has been approved by the vehicle manufacturer, see excerpts from EC vehicle approval (EC certificate of compliance). The load index, speed symbol, M+ S identification, the tire makes entered in the vehicle documentation and the remarks and recommendations of the vehicle manufacturer must be observed when this tire size is used.
- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.