

**Prüfbericht 366-0175-16-WIRD  
zur Erteilung der ECE (E1) 124R- 001060**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16556130-83

Stand: 19.04.2016



Seite: 1 von 2

**Manufacturer : MERCEDES-BENZ, VOLKSWAGEN**

**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 16 H2 Off set(mm) : 51

Hole circle (mm)/number of holes : 130/6 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1673	R1-1673	Without	84		1060	2163	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : MERCEDES-BENZ**

Mounting parts : spherical collar bolt M14x1,5, diameter 28,2 mm

Tightening torque for fixing parts : 180 Nm

commercial type: **SPRINTER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
906 AC 30	e1*2001/116*0353*..	80-190	205/75R16C 110		*) ; Station wagon; Rear-wheel drive; 1); 2); 33)
906 KA 30	L765	65-190	205/75R16C		*) ; Lkw box van (series); Rear-wheel drive; 1); 2); 33)
906 OK 30	L763	65-190	205/75R16C		*) ; pickup truck (series); 1); 2); 33)

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer : VOLKSWAGEN**

Mounting parts : spherical collar bolt M14x1,5, diameter 28,2 mm

Tightening torque for fixing parts : 180 Nm

commercial type: **CRAFTER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
2EC1	e1*2001/116*0355*..	65-120	205/75R16C		*) ; Rear-wheel drive; 1); 2); 33)
2EKE1	e1*2007/46*0513*..	65-120	205/75R16C		1); 2); 33)
2EKE1	L769	65-120	205/75R16C		*) ; Lkw box van (series); Rear-wheel drive; 1); 2); 33)
2FJE1	e1*2007/46*0521*..	65-120	205/75R16C		1); 2); 33)

**Prüfbericht 366-0175-16-WIRD**  
**zur Erteilung der ECE (E1) 124R- 001060**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16556130-83

Stand: 19.04.2016



Seite: 2 von 2

commercial type: **CRAFTER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
2FJE1	L767	65 -120	205/75R16C		*) ; pickup truck (series); Rear-wheel drive; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

### Restrictions

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.