

Prüfbericht 366-0572-15-WIRD
zur Erteilung der ECE (E1) 124R- 000819

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16704098-8

Stand: 16.12.2015



Seite: 1 von 1

Manufacturer : FIAT**Wheel dates:**

Wheel size according to standard : 7 J X 16 H2

Off set(mm) : 31

Hole circle (mm)/number of holes : 98/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1677	R1-1677	Without	58		560	1930	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad,
for Type : 198

Accessories : Serie

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad, for Type : 844;
198

Tightening torque for fixing parts : 100 Nm

commercial type: **FIAT BRAVO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
198	e3*2001/116*0248*..	66 -88	205/55R16 91H		1); 2); 33)
		110 -121	205/55R16 91V		
198	e3*2001/116*0288*..	66	205/55R16 91		1); 2); 33)

commercial type: **LANCIA DELTA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
844	e3*2001/116*0279*..	77 -140	205/55R16 91V		1); 2); 33)
		85 -140	195/55R16 91V		
844	e3*2007/46*0008*..	88	195/55R16 91V		1); 2); 33)
			205/55R16 91V		

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.