

**Prüfbericht 366-0095-16-WIRD
zur Erteilung der ECE (E1) 124R- 001069**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15555114-60

Stand: 09.03.2016



Seite: 1 von 2

Manufacturer : **HYUNDAI, HYUNDAI MOTOR (CZ), KIA MOTORS (SK)**

Wheel dates:

Wheel size according to standard : 5 1/2 J X 15 CH Off set(mm) : 47

Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1693	R1-1693	Without	67		545	1937	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **HYUNDAI, HYUNDAI MOTOR (CZ)**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **i 30,i 30CW**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
FD	e11*2001/116*0313*..	66 -93	185/65R15-88H		1); 2); 33)
			195/65R15 91H		
FDH	e11*2001/116*0343*..	66 -105	185/65R15-88H		1); 2); 33)
			195/65R15 91H		
FDH	e11*2007/46*0225*..	66 -94	185/65R15-88H		1); 2); 33)
			195/65R15 91H		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **KIA MOTORS (SK)**

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 108 Nm

commercial type: **CEE'D**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
ED	e4*2001/116*0121*..	66 -106	185/65R15-88H		1); 2); 33)
			195/65R15 91H		
ED	e4*2007/46*0132*..	66 -106	185/65R15-88H		1); 2); 33)
			195/65R15 91H		

Restrictions

- To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.

**Prüfbericht 366-0095-16-WIRD
zur Erteilung der ECE (E1) 124R- 001069**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15555114-60

Stand: 09.03.2016



Seite: 2 von 2

- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.