

Prüfbericht 366-0525-15-WIRD/N2
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000823

ANLAGE: 9.9
 Hersteller: MW Aftermarket Srl

Radtyp: 15554100-16
 Stand: 28.10.2015



Seite: 1 von 2

Manufacturer : OPEL / VAUXHALL, SUZUKI

Wheel dates:

Wheel size according to standard : 5 1/2 J X 15 CH Off set(mm) : 50
 Hole circle (mm)/number of holes : 100/4 centering type : centering fixed

Technical dates, short form

| version | Version name | | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|---------|----------------------|--------------------------|---------------------|--------------------|-----------------------------|--|----------------------------|
| | Wheel identification | Centering identification | | | | | |
| R1-1717 | R1-1717 | Without | 54 | | 425 | 1840 | 47/14 |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : OPEL / VAUXHALL

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Accessories : Serie

Tightening torque for fixing parts : 110 Nm

commercial type: **AGILA**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|-------|---------------|-----------------------|-------------------------------------|
| H-B | e4*2001/116*0135*.. | 48-69 | 185/60R15 84H | | *) ; Front wheel drive; 1); 2); 33) |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : SUZUKI

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : EX

Accessories : Serie

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad, for Type : EX

Tightening torque for fixing parts : 85 Nm

commercial type: **SPLASH**

| Vehicle type | Approval | kW | Tires | Restrictions of tires | Restrictions |
|--------------|---------------------|-------|---------------|-----------------------|--------------|
| EX | e4*2001/116*0130*.. | 48-69 | 185/60R15 84H | | 1); 2); 33) |
| EX | e4*2007/46*0283*.. | 66-69 | 185/60R15 84H | | 1); 2); 33) |

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- To be kept:
 - the standard wheel size and offset.

Prüfbericht 366-0525-15-WIRD/N2
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000823

ANLAGE: 9.9
Hersteller: MW Aftermarket Srl

Radtyp: 15554100-16
Stand: 28.10.2015



Seite: 2 von 2

- tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.