

Prüfbericht 21-00028-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837

ANLAGE: 9.3
 Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41
 Stand: 29.09.2022



Auto Service

Seite: 1 von 5

Manufacturer : SEAT, SEAT, S.A., SKODA, VOLKSWAGEN

Wheel dates:

Wheel size according to standard : 6 J X 15 H2 Off set(mm) : 38
 Hole circle (mm)/number of holes : 100/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1727	R1-1727	Without	57		500	1857	25/22

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : SEAT, SEAT, S.A.

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 120 Nm

commercial type: **IBIZA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6J	e9*2001/116*0067*..	55 - 81	185/60R15		*); from e9*2001/116*0067*32; Station wagon; Hatchback; Front wheel drive; 744; 77E; BF3; 1); 2); 33)
		55 - 110	185/60R15 M+S		
6J	e9*2001/116*0067*..	132	185/60R15 88		744; 77E; BF3; 1); 2); 33)
			185/60R15 88 M+S		
6J	e9*2001/116*0067*..	132	185/60R15 88		744; 77E; 1); 2); 33)
			185/60R15 88 M+S		
6J	e9*2001/116*0067*..	44 - 110	185/60R15		744; 77E; 1); 2); 33)
			185/60R15 M+S		
		59	175/65R15 84	ECO	
		66 - 77	175/65R15		
		132	185/60R15 88	from e9*2001/116*0067*16	
			185/60R15 88 M+S	from e9*2001/116*0067*16	
6J	e9*2001/116*0067*..	44 - 132	185/60R15		*); from e9*2001/116*0067*21; 744; 77E; BF3; 1); 2); 33)
		77	175/65R15		

Prüfbericht 21-00028-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837

ANLAGE: 9.3
 Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41
 Stand: 29.09.2022



Auto Service

Seite: 2 von 5

commercial type: **IBIZA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6J	e9*2001/116*0067*..	44 - 77	185/60R15 84		*); Not Fz with "SeatSport" Bremse; from e9*2001/116*0067*21; 12K; 51G; 76W; 1); 2); 33)
		77	175/65R15 84		
		105 - 132	185/60R15 88		
6J	e9*2001/116*0067*..	44 - 110	185/60R15		*); only to e9*2001/116*0067*20; 12K; 51G; 76W; 1); 2); 33)
			185/60R15 M+S		
		55 - 77	175/65R15		
6J	e9*2001/116*0067*..	132	185/60R15 88		1); 2); 33)
			185/60R15 88		
			M+S		

commercial type: **TOLEDO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
NH	e11*2007/46*0251*..	66	195/55R15		*); from e11*2007/46*0251*01; Limousine; Front wheel drive; 12K; 51G; 76W; 1); 2); 33)
		77	195/55R15		
		90	195/55R15		
NH	e11*2007/46*0251*..	66	195/55R15		*); from e11*2007/46*0251*01; Limousine; Front wheel drive; 744; BF3; 1); 2); 33)
		77	195/55R15		
		90	195/55R15		
NH	e11*2007/46*0251*..	55 - 92	185/60R15		*); from e11*2007/46*0251*01; Front wheel drive; 12K; 51G; 76W; 1); 2); 33)
		66 - 90	195/55R15		
		66 - 92	185/60R15 M+S		
NH	e11*2007/46*0251*..	55 - 92	185/60R15		*); from e11*2007/46*0251*01; Limousine; Front wheel drive; 744; BF3; 1); 2); 33)
		66 - 92	195/55R15		
NH	e8*2007/46*0321*..	70 - 92	185/60R15		744; 77E; 1); 2); 33)
			185/60R15 M+S		
NH	e8*2007/46*0321*..	70 - 92	185/60R15		744; 77E; BF3; 1); 2); 33)
			185/60R15 M+S		

Manufacturer : SEAT, SEAT, S.A., SKODA, VOLKSWAGEN

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : SKODA

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Prüfbericht 21-00028-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837

ANLAGE: 9.3
 Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41
 Stand: 29.09.2022



Auto Service

Seite: 3 von 5

Tightening torque for fixing parts : 120 Nm

commercial type: **FABIA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5J	e8*2007/46*0319*..	44 - 92	185/60R15		744; 77E; BF3; 1); 2); 33)
			185/60R15 M+S		
			195/55R15 M+S		
5J	e8*2007/46*0319*..	44 - 92	185/60R15		12K; 51G; 76W; 77E; 1); 2); 33)
			185/60R15 M+S		
			195/55R15 M+S		
5J	e8*2007/46*0319*..	44 - 92	185/60R15		744; 77E; 1); 2); 33)
			185/60R15 M+S		
			195/55R15 M+S		

commercial type: **PRAKTIK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5J	N083	51 - 63	185/55R15 M+S		744; 1); 2); 33)
			195/55R15		

commercial type: **RAPID**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
NH	e11*2007/46*0250*..	66	195/55R15		*); Front wheel drive; 12K; 51G; 76W; 1); 2); 33)
		77	195/55R15		
		90	195/55R15		
NH	e11*2007/46*0250*..	55 - 92	185/60R15		*); RAPID SPACEBACK; Front wheel drive; 744; 1); 2); 33)
		66 - 92	195/55R15		
NH	e11*2007/46*0250*..	55 - 92	185/60R15		*); Front wheel drive; 12K; 51G; 76W; 1); 2); 33)
		66 - 90	195/55R15		
		66 - 92	185/60R15 M+S		
NH	e11*2007/46*0250*..	55 - 92	185/60R15		*); Limousine; Front wheel drive; 744; 1); 2); 33)
		66 - 92	195/55R15		
NH	e8*2007/46*0320*..	66 - 92	185/60R15		12K; 51G; 76W; 77E; 1); 2); 33)
			185/60R15 M+S		

commercial type: **ROOMSTER, FABIA, PRAKTIK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5J	e11*2001/116*0291*..	44 - 77	185/55R15 M+S		12K; 51G; 76W; 1); 2); 33)
			185/60R15		
			195/55R15		
5J	e11*2001/116*0291*..	44 - 81	185/60R15		*); from e11*2001/116*0291*26; 12K; 51G; 76W; 1); 2); 33)
5J	e11*2001/116*0291*..	44 - 81	185/60R15		744; BF3; 1); 2); 33)

Prüfbericht 21-00028-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837

ANLAGE: 9.3
 Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41
 Stand: 29.09.2022



Auto Service

Seite: 4 von 5

commercial type: **ROOMSTER, FABIA, PRAKTIK**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
5J	e11*2001/116*0291*..	44 - 77	185/55R15 M+S 195/55R15 85H		*) ; only to e11*2001/116*0291*25; 744; BF3; 1); 2); 33)
5J	e11*2007/46*0013*..	77	195/55R15 85H		*) ; Fabia station wagon; Scout; 12K; 51G; 76W; 1); 2); 33)
5J	e11*2007/46*0013*..	44 - 81	185/60R15		12K; 51G; 76W; 1); 2); 33)
5J	e11*2007/46*0013*..	44 - 81	185/60R15		744; 1); 2); 33)

Manufacturer : SEAT, SEAT, S.A., SKODA, VOLKSWAGEN

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : VOLKSWAGEN

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 6R

Accessories : Serie

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad,
for Type : 6R; 9N

Tightening torque for fixing parts : 120 Nm

commercial type: **POLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
6R	e1*2001/116*0510*..	44 - 103	185/60R15		744; BF3; 1); 2); 33)
		77 - 103	175/65R15		
		110	185/60R15 M+S		
6R	e1*2001/116*0510*..	132	185/60R15 M+S		12K; 51G; 76W; 1); 2); 33)
6R	e1*2001/116*0510*..	44 - 103	185/60R15		12K; 51G; 76W; 1); 2); 33)
		77 - 103	175/65R15		
		110	185/60R15 M+S		
6R	e1*2001/116*0510*..	44 - 77	185/60R15		744; 1); 2); 33)
6R	e1*2001/116*0510*..	132	185/60R15 M+S		744; BF3; 1); 2); 33)
6R	e1*2001/116*0510*..	44 - 103	185/60R15		12K; 51G; 76W; 1); 2); 33)
		55 - 132	185/60R15 M+S		
		77 - 103	175/65R15		
6R	e1*2007/46*0486*..	44 - 81	185/60R15		744; BF3; 1); 2); 33)
		110	185/60R15 M+S		
6R	e1*2007/46*0486*..	44 - 81	185/60R15		12K; 51G; 76W; 1); 2); 33)
		110	185/60R15 M+S		
6R	e1*2007/46*0486*..	44 - 77	185/60R15 84		12K; 51G; 76W; 1); 2); 33)
		77	185/60R15 84H		
6R	e1*2007/46*0486*..	51 - 77	185/60R15		12K; 51G; 76W; 1); 2); 33)

Prüfbericht 21-00028-CX-GBM-06
zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000837

ANLAGE: 9.3
 Hersteller: MW Aftermarket Srl

Radtyp: 15605100-41
 Stand: 29.09.2022



Auto Service

Seite: 5 von 5

commercial type: **VW POLO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
9N	e1*2001/116*0174*..	40 - 77	185/60R15 84		*) ; Polo-Fun; Polo-Cross; 12K; 51G; 76W; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 12K) The use of snow chains is only permitted if the latter have been approved by the vehicle manufacturer for this wheel/tire combination (cf. operating instructions).
- 51G) This wheel/tire combination may only be used if this tire has already been entered as the standard in vehicle documents or has been approved by the vehicle manufacturer, see excerpts from EC vehicle approval (EC certificate of compliance). The load index, speed symbol, M+ S identification, the tire makes entered in the vehicle documentation and the remarks and recommendations of the vehicle manufacturer must be observed when this tire size is used.
- 744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.
- 76W) The use of this wheel/tire combination is only permitted if this wheel/tire combination has been entered by the vehicle manufacturer in the vehicle documents already.
- 77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.
- BF3) The use of the wheels is not permitted on vehicle versions with brake disc diameter 310mm or larger on the front axle.
- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.