

**Prüfbericht 366-0516-15-WIRD  
zur Erteilung der ECE (E1) 124R- 000828**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 14554108-25

Stand: 27.08.2015



Seite: 1 von 1

**Manufacturer** : FORD**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 14 H2 Off set(mm) : 37,5

Hole circle (mm)/number of holes : 108/4 centering type : centering fixed

**Technical dates, short form**

| version | Version name         |                          | Centering hole (mm) | Centering material | Permissible wheel Load (kg) | Permissible rolling Circumference (mm) | Valid from Production date |
|---------|----------------------|--------------------------|---------------------|--------------------|-----------------------------|--|----------------------------|
|         | Wheel identification | Centering identification |                     |                    |                             |  |                            |
| R1-1738 | R1-1738              | Without                  | 63,35               |                    | 425                         | 1781                                   | 47/14                      |

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

**Scope/Vehicle Manufacturer** : FORD

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: FIESTA

| Vehicle type | Approval            | kW      | Tires         | Restrictions of tires | Restrictions |
|--------------|---------------------|---------|---------------|-----------------------|--------------|
| JA8          | e9*2001/116*0069*.. | 44 -103 | 175/65R14     |                       | 1); 2); 33)  |
| JA8-LPG      | e13*2007/46*1058*.. | 68 -71  | 175/65R14 M+S |                       | 1); 2); 33)  |
|              |                     |         | 175/65R14 82  |                       |              |
| JR8          | DE*2007/46*0072*..  | 50 -66  | 175/65R14 82  |                       | 1); 2); 33)  |
| JR8          | e9*2007/46*0002*..  | 50 -70  | 175/65R14 82  |                       | 1); 2); 33)  |

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.