

**Prüfbericht 366-0344-15-WIRD
zur Erteilung der ECE (E1) 124R- 001043**
ANLAGE: 9.2

Hersteller: MW Aftermarket Srl

Radtyp: 13504098-1

Stand: 06.10.2015



Seite: 1 von 1

Manufacturer : FIAT**Wheel dates:**

Wheel size according to standard : 5.00 B X 13 H Off set(mm) : 35
Hole circle (mm)/number of holes : 98/4 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1803	R1-1803	Without	58		375	1765	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : FIAT

Mounting parts : conical collar bolt M12x1,25, tapered thread 60 Grad

Tightening torque for fixing parts : 100 Nm

commercial type: **FIAT PANDA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
169	e3*2001/116*0151*..	40-55	155/80R13 79		*) ; Front wheel drive; 1); 2); 33)
169	e3*2001/116*0287*..	44	155/80R13 79		1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.