

**Prüfbericht 366-0214-16-WIRD
zur Erteilung der ECE (E1) 124R- 001068**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15655112-54

Stand: 11.05.2016



Seite: 1 von 2

Manufacturer : DAIMLER (D)**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 15 H2 Off set(mm) : 47

Hole circle (mm)/number of holes : 112/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1813	R1-1813	Without	66,5		550	1937	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : DAIMLER (D)

Mounting parts : spherical collar bolt M14x1,5, diameter 28,2 mm

Tightening torque for fixing parts : 130 Nm

commercial type: **A-KLASSE**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
176	e1*2007/46*0928*..	80	195/65R15 91		1); 2); 33)
		90	195/65R15 91H		

commercial type: **B-Klasse**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
246	e1*2007/46*0751*..	80-90	195/65R15 91		1); 2); 33)

commercial type: **B-KLASSE, B 180 NGT, A-KLASSE, CLA, GLA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
245G	e1*2001/116*0470*..	66-90	195/65R15		*) ; B-Klasse from Mj. 2011; Front wheel drive; 1); 2); 33)
245G	e1*2001/116*0470*..	66-90	195/65R15		*) ; A-Klasse; Front wheel drive; 1); 2); 33)
245G	e1*2001/116*0470*..	80-90	195/65R15		*) ; CLA Limousine; Front wheel drive; 1); 2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.

**Prüfbericht 366-0214-16-WIRD
zur Erteilung der ECE (E1) 124R- 001068**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 15655112-54

Stand: 11.05.2016



Seite: 2 von 2

- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.