

Prüfbericht 22-00097-CX-GBM-02**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001058****ANLAGE: 9.6**

Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18

Stand: 17.07.2023



Auto Service

Seite: 1 von 4

Manufacturer : SEAT, SKODA, VOLKSWAGEN**Wheel dates:**

Wheel size according to standard : 5 J X 14 H2

Off set(mm) : 35

Hole circle (mm)/number of holes : 100/4

centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1829	R1-1829	Without	57		405	1793	05/22

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : SEAT

Mounting parts : spherical collar bolt M12x1,5, diameter 26 mm

Tightening torque for fixing parts : 110 Nm

commercial type: **MII**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AA	e13*2007/46*1168*..	44 - 55	165/70R14	12K; 51G	10B; 11H; 11N; 51A; 744; 76V; 77E; BF2; 1); 2); 33)
			175/65R14	51G	
AA	e13*2007/46*1168*..	44 - 55	165/70R14		744; 77E; BF2; 1); 2); 33)
			175/65R14		
		61	165/70R14		
AAN	e13*2007/46*1183*..	55	165/70R14 81		BF2; 1); 2); 33)
			175/65R14 82		
AAN	e13*2007/46*1183*..	44 - 55	165/70R14		744; BF2; 1); 2); 33)
			175/65R14		

Manufacturer : SEAT, SKODA, VOLKSWAGEN

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : SKODA

Mounting parts : spherical collar bolt M12x1,5, diameter 26 mm

commercial type: **CITIGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AA	e13*2007/46*1169*..	44 - 55	175/65R14		744; 77E; BF2; 1); 2); 33)
		44 - 61	165/70R14		
			165/70R14 M+S		
AA	e13*2007/46*1169*..	44 - 55	165/70R14		744; 77E; BF2; 1); 2); 33)
			165/70R14 M+S		
			175/65R14		

Prüfbericht 22-00097-CX-GBM-02**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001058****ANLAGE: 9.6**

Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18

Stand: 17.07.2023



Auto Service

Seite: 2 von 4

commercial type: **CITIGO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AAN	e13*2007/46*1184*..	44 - 55	165/70R14	12K; 51G	10B; 11H; 11N; 51A; 744; 76V; BF2; 1); 2); 33)
			175/65R14	51G	
AAN	e13*2007/46*1184*..	55	165/70R14 81		744; BF2; 1); 2); 33)
			175/65R14 82		

Manufacturer : SEAT, SKODA, VOLKSWAGEN

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : VOLKSWAGEN

Mounting parts : spherical collar bolt M12x1,5, diameter 26 mm

Tightening torque for fixing parts : 110 Nm

commercial type: **UP!**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AA	e13*2007/46*1167*..	60 - 61	165/70R14 M+S		744; 77E; BF2; 1); 2); 33)
AA	e13*2007/46*1167*..	44 - 66	165/70R14	12K; 51G	10B; 11H; 11N; 51A; 744; 76V; 77E; BF2; 1); 2); 33)
			175/65R14	51G	
AA	e13*2007/46*1167*..	60	165/70R14 M+S	12K; 51G; 52J	*) ; e-up!; 10B; 11H; 11N; 51A; 76V; BF2; 1); 2); 33)
AA	e13*2007/46*1167*..	60	165/70R14 M+S		744; 77E; BF2; 1); 2); 33)
AA	e13*2007/46*1167*..	55	165/70R14		744; 77E; BF2; 1); 2); 33)
			175/65R14		
AA	e13*2007/46*1167*..	55	165/70R14		744; 77E; BF2; 1); 2); 33)
			175/65R14		
AA	e13*2007/46*1167*..	44 - 50	175/65R14		744; 77E; BF2; 1); 2); 33)
		44 - 61	165/70R14		
			165/70R14 M+S		
AA	e13*2007/46*1167*..	44 - 55	165/70R14		744; 77E; BF2; 1); 2); 33)
			175/65R14		
		66	165/70R14		
			175/65R14		
AA	e13*2007/46*1167*..	44 - 66	165/70R14		744; 77E; BF2; 1); 2); 33)
			175/65R14		
		55 - 66	165/70R14 M+S		
AA	e13*2007/46*1167*..	60	165/70R14 M+S		744; 77E; BF2; 1); 2); 33)
AAN	e13*2007/46*1182*..	60	165/70R14 M+S		744; 77E; 1); 2); 33)
AAN	e13*2007/46*1182*..	60	165/70R14 M+S	12K; 51G; 52J	*) ; e-up!; 10B; 11H; 11N; 51A; 744; 76V; 77E; BF2; 1); 2); 33)

Prüfbericht 22-00097-CX-GBM-02**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001058****ANLAGE: 9.6**

Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18

Stand: 17.07.2023



Auto Service

Seite: 3 von 4

commercial type: **UP!**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
AAN	e13*2007/46*1182*..	44 - 55	165/70R14	12K; 51G	10B; 11H; 11N; 51A;
			175/65R14	51G	744; 76V; 77E; BF2; 1); 2); 33)
AAN	e13*2007/46*1182*..	44 - 55	165/70R14		744; 77E; BF2; 1);
			175/65R14		2); 33)
AAN	e13*2007/46*1182*..	44 - 55	165/70R14		744; 77E; BF2; 1);
			175/65R14		2); 33)
AAN	e13*2007/46*1182*..	60	165/70R14 M+S		744; 77E; BF2; 1);
					2); 33)

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale - names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 10B) Apart from tires with an M + S tread, the required minimum speed ranges for the tires to be used, taking load indexes into consideration, can be found in the vehicle documentation, unless deviations have been defined in the scope of application.
- 11H) If the standard spare wheel is used, the car should be driven at moderate speed and for no longer than necessary. The wheel must be fitted with standard fastening elements. When the spare wheel is used on four-wheel-drive vehicles, care should be taken to use only tires with identically sized rolling circumference.
- 11N) The brake and steering systems and the suspension, except for custom suspension springs, must be standard, unless governed by other requirements.
- 12K) The use of snow chains is only permitted if the latter have been approved by the vehicle manufacturer for this wheel/tire combination (cf. operating instructions).
- 51A) The inflation pressure specified by the vehicle manufacturer (see operating instructions or tire inflation pressure indicated on the vehicle) or tire manufacturer must be observed. According to the manufacturer, tires with run-flat properties may only be used in combination with a tire inflation monitoring system.
- 51G) This wheel/tire combination may only be used if this tire has already been entered as the standard in vehicle documents or has been approved by the vehicle manufacturer, see excerpts from EC vehicle approval (EC certificate of compliance). The load index, speed symbol, M+ S identification, the tire makes entered in the vehicle documentation and the remarks and recommendations of the vehicle manufacturer must be observed when this tire size is used.
- 52J) This tire size is only permitted with M+S tread
- 744) The tightening torque of the custom wheels' fastening elements is specified in the vehicle's operating manual. Should no tightening torque be specified there, the tightening torque quoted in the expert report shall apply.
- 76V) The use of this tire size and offset is only permitted if used as standard.
- 77E) The indirect Tire Pressure Monitoring system must be calibrated. The instructions of the manual must be followed.
- BF2) The use of the wheels is not permitted on vehicle versions with brake disc diameter 288mm or larger on the front axle.
- 1) To be kept:
- the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments

Prüfbericht 22-00097-CX-GBM-02

zur Erteilung eines Nachtrags zur ECE (E1) 124R- 001058

ANLAGE: 9.6

Hersteller: MW Aftermarket Srl

Radtyp: 14504100-18

Stand: 17.07.2023



Auto Service

Seite: 4 von 4

- as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.