

**Prüfbericht 366-0096-16-WIRD/N1**  
**zur Erteilung der ECE (E1) 124R- 001083**

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16556205-85

Stand: 25.05.2016



Seite: 1 von 2

**Manufacturer** : DAIMLER (D)**Wheel dates:**

Wheel size according to standard : 5 1/2 J X 16 H2 Off set(mm) : 111

Hole circle (mm)/number of holes : 205/6 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1859	R1-1859	Without	161		1060	2163	47/14
R1-1859 MWRO	R1-1859	Without	161		1060	2163	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer** : DAIMLER (D)

Mounting parts : Flachbundmuttern M14x1,5

Tightening torque for fixing parts : 170 Nm

commercial type: **SPRINTER 310..313..316 CDI**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
906BB50	e1*2007/46*0295*..	70-120	195/75R16C 107 205/75R16C 110		*) Zwillingsbereifung; 1); 2); 33)

commercial type: **SPRINTER 310..313..316..319..326 CDI**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
906BA50	e1*2007/46*0299*..	70-140	195/75R16C 107 205/75R16C 110		*) Zwillingsbereifung; 1); 2); 33)

commercial type: **SPRINTER 4X4 313..316..319 CDI**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
906BA50/4x4	e1*2007/46*0311*..	95-140	205/75R16C 110		*) Zwillingsbereifung; 1); 2); 33)
906BB50/4x4	e1*2007/46*0307*..	95-140	205/75R16C 110		*) Zwillingsbereifung; 1); 2); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

**Restrictions**

- To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.

**Prüfbericht 366-0096-16-WIRD/N1  
zur Erteilung der ECE (E1) 124R- 001083**

**ANLAGE: 9.1**

Hersteller: MW Aftermarket Srl

Radtyp: 16556205-85

Stand: 25.05.2016



Seite: 2 von 2

- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.