

**Prüfbericht 366-0556-15-WIRD/N2**  
**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000849**

ANLAGE: 9.3

Hersteller: MW Aftermarket Srl

Radtyp: 16605114-64

Stand: 23.11.2017



Seite: 1 von 1

**Manufacturer : SUZUKI****Wheel dates:**

Wheel size according to standard : 6 J X 16 CH Off set(mm) : 50

Hole circle (mm)/number of holes : 114,3/5 centering type : centering fixed

**Technical dates, short form**

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1878 MWRO	R1-1878	Without	60		535	1990	47/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

**Scope/Vehicle Manufacturer : SUZUKI**

Mounting parts : conical collar bolt M12x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 85 Nm

commercial type: **SX4, SUZUKI SX4**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
JY	e4*2007/46*0779*..	88	205/60R16		*) SX4 S-Cross; to e4*2007/46*0779*03; 1); 33)

\*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale- names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

**Restrictions**

- 1) To be kept:
  - the standard wheel size and offset.
  - tyre size with service description (load and speed index) and tyre brand commitments
  - as well as limitations to snow tyres (M+S) from the car documents.
  - requirements and limitations of snow chains from the operating licence and the operation manual.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.