

Prüfbericht 20-00295-CX-GBM-06**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840****ANLAGE: 9.5**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 02.08.2023



Auto Service

Seite: 1 von 2

Manufacturer : FORD**Wheel dates:**

Wheel size according to standard : 6 1/2 J X 16 H2 Off set(mm) : 50
 Hole circle (mm)/number of holes : 108/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1886	R1-1886	Without	63,35		678	1989	51/14

Prescribed systems in the vehicle must be functioning with the use of the described rim combination.

Scope/Vehicle Manufacturer : FORD

Mounting parts : conical collar nut M12x1,5, tapered thread 60 Grad,
for Type : PU2; DM2

Mounting parts : conical collar nut M14x1,5, tapered thread 60 Grad, for Type : PJ2

Tightening torque for fixing parts : 120 Nm for Type : PJ2; PU2
 120 Nm (Nur C-MAX) for Type : DM2
 130 Nm for Type : DM2

commercial type: **FORD C-MAX / KUGA**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
DM2	e13*2001/116*0109*..	100 - 120	235/60R16 100		*); til modelyear 2012; until e13*2001/116*0109*31; All-wheel drive; Front wheel drive; 1); 2); 33)
		147	235/60R16 91V		
DM2	e13*2001/116*0109*..	85 - 134	215/65R16		*); Only Kuga from Modelyear 2013; from e13*2001/116*0109*31; 1); 2); 33)
			235/60R16		
DM2	e13*2001/116*0109*..	66 - 107	205/55R16 91		*); C-MAX only; 1); 2); 33)
		81 - 107	205/55R16 M+S		

commercial type: **TOURNEO CONNECT, TRANSIT CONNECT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
PJ2	e1*2001/116*0207*..	55 - 125	205/60R16		1); 2); 33)
			205/60R16 M+S		
			215/55R16		
			215/55R16 M+S		

Prüfbericht 20-00295-CX-GBM-06**zur Erteilung eines Nachtrags zur ECE (E1) 124R- 000840****ANLAGE: 9.5**

Hersteller: MW Aftermarket Srl

Radtyp: 16655108-45

Stand: 02.08.2023



Auto Service

Seite: 2 von 2

commercial type: **TRANSIT CONNECT,TOURNEO CONNECT**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
PU2	e1*2007/46*0272*..	55 - 110	205/60R16		1); 2); 33)
			205/60R16 M+S		
			215/55R16		
			215/55R16 M+S		

*) The remarks under the listed restrictions/conditions are to be kept. If additional trademarks or sale - names are listed, so there are only this vehicles permissible. All other vehicles to this one application are not concerned.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.