

Prüfbericht 366-0369-15-WIRD
zur Erteilung der ECE (E1) 124R- 001061

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605118-33

Stand: 28.10.2015



Seite: 1 von 2

Manufacturer : **CITROEN, FIAT, PEUGEOT**

Wheel dates:

Wheel size according to standard : 6 J X 16 H2 Off set(mm) : 68

Hole circle (mm)/number of holes : 118/5 centering type : centering fixed

Technical dates, short form

version	Version name		Centering hole (mm)	Centering material	Permissible wheel Load (kg)	Permissible rolling Circumference (mm)	Valid from Production date
	Wheel identification	Centering identification					
R1-1909	R1-1909	Without	71		1100	2269	47/14

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **CITROEN**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **JUMPER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2007/46*0046*..	88 -116	215/75R16C		*); van; Front wheel drive; 1); 2); 33)
			116R		
			225/75R16C		
		96 -107	225/75R16C		
			118R		
107	225/75R16CP				
			116Q		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **FIAT**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

Prüfbericht 366-0369-15-WIRD
zur Erteilung der ECE (E1) 124R- 001061

ANLAGE: 9.1

Hersteller: MW Aftermarket Srl

Radtyp: 16605118-33

Stand: 28.10.2015



Seite: 2 von 2

commercial type: **FIAT DUCATO**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
250	e3*2007/46*0044*..	88 -116	215/75R16C		*); van; Front wheel drive; 1); 2); 33)
			116R		
			225/75R16C		
		116R			
		225/75R16C			
		96 -107	225/75R16C		
			118R		
		107	225/75R16C		
			118Q		
			225/75R16CP		
			116Q		

In built-up vehicle safety and / or environment-related vehicle systems (such as tire pressure monitoring systems) must remain functional or replaced.

Scope/Vehicle Manufacturer : **PEUGEOT**

Mounting parts : conical collar bolt M14x1,5, tapered thread 60 Grad

Tightening torque for fixing parts : 160 Nm

commercial type: **BOXER**

Vehicle type	Approval	kW	Tires	Restrictions of tires	Restrictions
Y	e3*2007/46*0045*..	88 -116	215/75R16C		*); van; Front wheel drive; 1); 2); 33)
			116R		
			225/75R16C		
		116R			
		225/75R16C			
		96 -107	225/75R16C		
			118R		
		107	225/75R16C		
			118Q		
			225/75R16CP		
			116Q		

*) The remarks under the listed restrictions/conditions are to be kept. Furthermore only the vehicles (trade name or trademark listed in the conditions) are covered which are also listed in the field of applications.

Restrictions

- 1) To be kept:
 - the standard wheel size and offset.
 - tyre size with service description (load and speed index) and tyre brand commitments
 - as well as limitations to snow tyres (M+S) from the car documents.
 - requirements and limitations of snow chains from the operating licence and the operation manual.
- 2) Only permissible at vehicle models, which are allowed to use steel wheels as standard.
- 33) The standard fixing parts and accessories of the vehicle manufacturer for the corresponding series-wheel must be used.